



RE PER UNIT: 2  
 USED ON: MODEL VLRB-1  
 ASSY. NO. A3653  
 DATE: 4-12-65

AC 182 Ø



ELECTRICAL SPECS.  
(WITH SLUG INSERTED)

OPERATING FREQUENCY:  
 INDUCTANCE @ 790 KC  
 PRIMARY: 235 UH ± 4 UH  
 SECONDARY: NOT RATED  
 "Q" (PRIMARY) @ 100 KC : > 55

MECHANICAL SPEC.

TURNS  
 PRIMARY: 129  
 SECONDARY: —  
 COLOR CODE: GREY  
 CASE: COPPER CAN  
 CASE FINISH: TIN-PLATED  
 QUANTITY TERM: 4  
 MATERIAL:  
 CORE & SLUG: POWDERED IRON

SCHEMATIC



REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
Ø		ORIGINAL RELEASE FOR PRODUCTION	
X		EXPER. RELEASE	

REQUISITION NO.	ITEM NO.	QUANTITY	UNIT	DESCRIPTION	SYMBOL
				THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
				COIL, RF, ADJUSTABLE	

DATE: 4/24/65  
 SCALE: X  
 CHECKER: [Signature]  
 DRAFTS: [Signature]  
 CODE: A  
 TOLERANCES: ± 1/64 ANGLES, ± 0° 30'  
 DECIMALS: .X ± .05  
 .XX ± .01  
 .XXX ± .005  
 2A3889