REQ. PER UNIT	USED ON MODEL	ASS'Y. NO.	DATE		
1	VLRB-1	A-3681	3-17-65	AC 194	Ø







ELECTRICAL SPECS.
(WITH SLUG INSERTED)

OPERATING FREQUENCY:
INDUCTANCE @ 790 KCS
PRIMARY: 446 µh ±10µh
SECONDARY: NOT RATED
"Q" (PRIMARY)@ 250 KCS: >60

MECHANICAL SPEC.

TURNS
PRIMARY: 198
SECONDARY:
COLOR CODE: GREY
CASE: COPPER CAN
CASE FINISH: TIN-PLATED
QUANTITY TERM: 4
MATERIAL:
CORE & SLUG: POWDERED IRON



SCHEMATIC DIAGRAM

SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
Ø	ORIGINAL RELEASE FOR PRODUCTION	4.7.65	Ø			
X	EXPER. RELEASE	3.17.65	X	HLA		

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

SCALE

DECIMALS .X ±.05 .XX ± .01 .XXX ±.005 TOLERANCES FRACTIONS ± 1/64 ANGLES ± 0° 30'

CODE A

2-A-3922

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL

STOCK SIZE —

MATERIAL —

TYPE & TEMPER — HEAT TREAT. SPEC. —

FINISH & SPEC. NO. —

THE TECHNICAL MATERIEL CORP.
MAMARONECK, NEW YORK

COIL, RF, ADJUSTABLE

DRAWN	CHECKED	FINAL APPROVAL
H. Austin	3-29-65	

ELEC. DES. APP. MCB — MECH. DES. APP.

AC 194 Ø

REPROVEL NO. 440H 16106