IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES

A- 11/64 (.171) DIA. 6 HOLES REQ.
B- 1/2 (.500) " 4 " "
C- DRILL & C'SINK 4-40 F.H.S. 4 " "
D- " & " 6-32 " 13 " "
E- 3/16 X 1/4 SLOT 7 " "
F- 3/16 (.187) DIA. 7 " "
G- 7/8 (.875) " . 1 " "

J-#AB(.076) DIA. 2 HOLES REQ. FOR CANADIAN UNITS ONLY.

NOTE: C & D HOLES MUST BE SO COUNTERSUNK THAT SCREW HEAD IS 1/64 BELOW SURFACE.

NOTE:
OUTSIDE DIMENSIONS MUST BE HELD TO TOLERANCES SPECIFIED.

NOTICE TO PERSONS RECEIVING THIS DRAWING

THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.

Property of:
THE TECHNICAL MATERIEL CORPORATION
MAMARONECK, NEW YORK

ALL BENDS 90° WITH 1/16 INSIDE RADIUS

REF: A-1256 BOTTOM COVER

NOTE:
MS-911-1 AS SHOWN.
MS-911-2 FOR CANADIAN UNITS ONLY. SEE BELOW FOR ADDED HOLES.

ISSUE	ITEM	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENG. APP.
A	1	S-404 IRIDITE WAS S-101 CAUSTIC DIP	12/6/57	1001	AB		EMN

TOLERANCES: ALL OTHERS — DEC. DIM. ± .005; FRAC. DIM. ± 1/64; ANGULAR DIM. ±

SCALE: DRILL, PUNCH, COMMERCIAL STOCK SIZES AND MANUFACTURERS TOLERANCES ARE NOT INCLUDED.

FORM — 111

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
7	2	NT-108-2 NUT, SPEED	
X	1	MS-911 HEAD FRAME (NO DWG.)	
.064		THE TECHNICAL MATERIEL CORP. MAMARONECK. NEW YORK	
STOCK SIZE			
ALUMINUM		HEAD FRAME SUB ASSY.	
MATERIAL	WEIGHT PER PC.		
52S H32		CDD 3/21/56	
TYPE & TEMPER		DRAWN: R.L.K. 3-20-56	ELEC. DES. APP. / MECH. DES. APP.
HEAT TREAT. SPEC.		CHECKED: JAH	FINAL APPROVAL
S-404 IRIDITE			A-1257 A
FINISH & SPEC. NO.			

REQ PER UNIT	MODEL	PROJECT NO.	ASS'Y. NO.	DATE
1	FRRD-1, 2, 3	E-458-P		3-21-56

USED ON

A-1257 | A