



NOTES -
LUGS SHOWN ROTATED FOR CLARITY.
ITEMS CALLED OUT IN ORDER OF ASSEMBLY.

NOTICE TO PERSONS RECEIVING THIS DRAWING
THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.

Property of:
THE TECHNICAL MATERIEL CORPORATION
MAMARONECK, NEW YORK

REQ. UNIT	ITEM	PART NO.	DESCRIPTION	SYMBOL
3	36	SCBP1032BN10	Screw, Machine	
2	35	MS-2488	Bracket, Mtg.	
2	34	TE-141-4	Terminal, Lug.	
X	33	WL-100-4	Wire, Buss	
6	32	FWO4HBN	Washer, Flat	
6	31	NTH0440BN6	Nut, Hex.	
6	30	LWE04MRN	Lockwasher, Ext.	
6	29	SCBP0440BN7	Screw, Machine	
1	28	CA-409-46-3.50	Cable Assy. Jumper	BIK
1	27	-48-5.50	↓ ↓ ↓	Wh
1	26	-49-6.00	↓ ↓ ↓	Wh/Bik
1	25	CA-409-50-6.00	Cable Assy. Jumper	Wh.
2	24	NTH0832BN10	Nut, Hex.	
4	23	FWO8HBN	Washer, Flat	
4	22	LWE08MRN	Lockwasher, Ext.	
2	21	SCBP0832BN16	Screw, Machine	
6	20	TE-104-4	Lug, Solder	
3	19	SCBP1032BN14	Screw, Machine	
25	18	NTH1032BN12	Nut, Hex.	
29	17	LWE10MRN	Lockwasher, Ext.	
26	16	FW10HBN	Washer, Flat	
5	15	SCBP1032BN16	Screw, Machine	
1	14	CA-409-192-4.00	Cable Assy. Jumper	Wh/Bik
1	13	-51-6.00	↓ ↓ ↓	Wh
1	12	-52-6.00	↓ ↓ ↓	Wh/Bik
1	11	CA-409-191-3.50	Cable Assy. Jumper	Wh/Bik
2	10	MS-2487	Buss-Bar Fixed	
1	9	RW-109-32	Resistor, Fixed (5K, 10W)	R503
2	8	AR-134	Shunt Assy, Power Input	R501 R502
2	7	CA-409-50-8.00	Cable Assy. Jumper	White
3	6	MS-2486	Buss-Bar, Switching	
9	5	PM-677	Terminal, bushing Type	
9	4	SCBP1032BN6	Screw, Machine	
4	3	CM35F103F03	Capacitor, Fixed, Mica	C521, C522 C523, C524
2	2	CL-269	Choke, RF	L521 L522
1	1	PX-600 (LD-897)	Board, Mtg.	

SYM	ZONE	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
B		ITEMS 3, 4, 14, 19, 21, 22, 23, 26 UPDATED	3-2-67	1762	LAK		
A	24	R501 WAS R502, R502 WAS R501	10-2-61	866B	LB	RK	

UNLESS OTHERWISE SPECIFIED:
SCALE

DIMENSIONS ARE IN INCHES
TOLERANCES ON FRACTIONS ± 1/64 DECIMALS ± .005 ANGLES ± 1/2°

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS & SHARP EDGES

REQ. UNIT	MODEL	SECTION	ASSY. NO.	DATE
1	APP-5			3-28-61

TYPE & TEMPER	HEAT TREAT. SPEC.	FINISH & SPEC. NO.	ELEC. DES. APP.	MECH. DES. APP.	SHEET	OF
					A-2077	B