



* FRONT & REAR TERMINALS TIED TOGETHER WITH ITEM 14.

NOTE ~ MAKE ALL BUSS-WIRE LENGTHS 3/4" LONGER THEN SPECIFIED SLEEVING LENGTHS.

X	17	BS-100	Solder, Soft	
X	16	PX-104-4-.053	Sleeving, Insulation	Green
X	15	WL-100-4	Wire, Buss-Bar, Tinned	
X	14	WL-100-7	Wire, Buss-Bar, Tinned	
X	13	PX-104-1-.034	Sleeving, Insulation	Black
X	12			Red
X	11			Blue
X	10			Yellow
X	9	PX-104-4-.034	Sleeving, Insulation	Green
2	8	NTH0440BN6	Nut, Hex	
2	7	LWS04MRN	Lockwasher, Split	
2	6	TE-117-21	Spacer	
8	5	WA-109-17	Washer, Fibre	
2	4	SCBP0440BN10	Screw, Machine	
1	3	CC100-32	Capacitor, Fixed, Ceramic	
1	2	WS-101	Wafer, Switch	
1	1	MS-2638(LD-962)	Bracket, Switch Mount	

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
STOCK SIZE			THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK RF SWITCH ASSEMBLY 3RD STAGE	
MATERIAL				
TYPE & TEMPER				
HEAT TREAT. SPEC.			DRAWN: <i>[Signature]</i> CHECKER: <i>[Signature]</i> FINAL APPROVAL: <i>[Signature]</i>	
FINISH & SPEC. NO.			ELEC. DES. APP.	MECH. DES. APP.

A	ITEM 3 WAS CMISC511J	2/10/66	15740	Jc	<i>[Signature]</i>	<i>[Signature]</i>
SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
UNLESS OTHERWISE SPECIFIED:		SCALE:				
DIMENSIONS ARE IN INCHES		MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION.				
TOLERANCES ON FRACTIONS ± 1/64		DECIMALS ± .005				
ANGLES ± 1/2°		REMOVE ALL BURRS AND SHARP EDGES				
		1	GPE-1			10-20-61
		REQ. PER UNIT	MODEL	SECTION	ASS'Y. NO.	DATE
		USED ON				