

A

A3280

USED ON
ASSY. NO. A2786
DATE 10/28/64

MODEL
TTR-10/
AX418

REQ. PER UNIT
1

SYMBOL(S)	ITEM NO.	USED TO MOUNT	QTY
R1537	4		
R1541	5		
R1539	6		
R1538	7		
R1540	8		
S1505	9		
	10	SW340	1

WIRE, ELECTRICAL, BUSS, SIZE 24
 TERMINAL, LUG-3/8D
 SWITCH, ROTARY
 RESISTOR, FIXED, COMPOSITION
 RESISTOR, FIXED, COMPOSITION
 RESISTOR, FIXED, COMPOSITION
 RESISTOR, FIXED, COMPOSITION
 RESISTOR, FIXED, COMPOSITION
 RESISTOR, FIXED, COMPOSITION
 INSULATION SLEEVING, SIZE 24-VIOLET
 INSULATION SLEEVING, SIZE 24-RED
 SOLDER, TIN ALLOY

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
3	WL100-8	WIRE, ELECTRICAL, BUSS, SIZE 24	
1	TE111-2	TERMINAL, LUG-3/8D	
1	SW340	SWITCH, ROTARY	
1	RC20GF750J	RESISTOR, FIXED, COMPOSITION	
1	RC20GF103J	RESISTOR, FIXED, COMPOSITION	
1	RC20GF470J	RESISTOR, FIXED, COMPOSITION	
1	RC20GF331J	RESISTOR, FIXED, COMPOSITION	
1	RC20GF114J	RESISTOR, FIXED, COMPOSITION	
1	PX104-9-022	INSULATION SLEEVING, SIZE 24-VIOLET	
2	PX104-3-022	INSULATION SLEEVING, SIZE 24-RED	
1	BS100	SOLDER, TIN ALLOY	
A		AAET	SYMBOL
A		THE TECHNICAL MATERIEL CORP. MAMARONECK. NEW YORK	
Ø		MODE SWITCH ASSEMBLY	
SYM		DESCRIPTION	
A		10-30-64	10-30-64
Ø		ENG COORD	10-30-64
SYM		DRAWN	10-30-64
A		CHECKED	10-30-64
Ø		TYPE & TEMPER	HEAT TREAT. SPEC
SYM		FINISH & SPEC. NO.	A3280
A		ELEC. DES. APP.	Mech. Des. App.
Ø		FINAL APPROVAL	A

UNLESS OTHERWISE SPECIFIED
 DIMENSIONS ARE IN INCHES AND INCLUDE
 CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES
 DECIMALS ± .05
 FRACTIONS ± 1/64
 ANGLES ± 0° 30'

SCALE
 DATE 11-2-64
 CH. NO. Ø
 DRAFTS 9#
 CHECKER Jpb
 ENG. APP.

ORIGINAL RELEASE FOR PRODUCTION
 6/2/85
 14106

108-A

CURRENCY NO. 140M 16323