REQ. PER UNIT	USED ON MODEL	ASS'Y. NO.	DATE		
1	MSR-9		10/1/64	A3290	A

SYMBOL(S)	ITEM NO.	USED TO MOUNT	QTY
	6	A2725 to A3299	4
		A3291 to A3299	5
		A3292 to A3299	5
P4	10		
	11	A2725 to A3299	4
		A3291 to A3299	5
		A3292 to A3299	5
	12	A3291 to A3292	1
		A3291 to A2725	1
	13	A2725 to A3299	4
		A3292 to A3299	2
	14	A3291 to A3292	3
		A3291 to A2725	3
	15	A3292 to A3299	3
P1	16		

LOOSE ITEM	1	16	UG260*/U	CONNECTOR,PLUG-BNC	
	3	15	SCFP0832BN6	SCREW,MACHINE	
	6	14	SCBP0832BN7	SCREW,MACHINE	
	6	13	SCBP0832BN6	SCREW,MACHINE	
	2	12	PM236-2B	BAR,PNL LKG	
	14	11	NTH0832BN10	NUT,PLAIN,HEX	
LOOSE ITEM	1	10	MS3106A14S 2S	CONNECTOR,PLUG,FEMALE	
LOOSE ITEM	1	9	MS3057-6	CLAMP,CABLE,EL CONNECTOR	
	1	8	MS1327	COVER,BOTTOM	
	1	7	MS1323	COVER,TOP	
	14	6	LWE08MRN	WASHER,LOCK,EXTERNAL	
LOOSE ITEM	1	5	CA1079	CABLE ASSEMBLY,POWER,AC	W1
	1	4	A3299	CHASSIS ASSEMBLY,MAIN	
	1	3	A3292	PLATE ASSEMBLY,LEFT SIDE	
	1	2	A3291	PANEL ASSEMBLY,FRONT	
	1	1	A2725	POWER SUPPLY,ASSEMBLY	

SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
A	ITEM 5 WAS CA385	328-67	18047	L.A.K.		
Ø	ORIGINAL RELEASE FOR PRODUCTION	10.7.64	Ø	J.L.		

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

SCALE

TOLERANCES: DECIMALS .X ±.05, .XX ±.01, .XXX ±.005; FRACTIONS ± 1/64; ANGLES ± 0° 30′

CODE

REQ.	ITEM	PART NO.	DESCRIPTION	SYMB L
			POSE	

STOCK SIZE

MATERIAL

TYPE & TEMPER | HEAT TREAT. SPEC.

FINISH & SPEC. NO.

THE TECHNICAL MATERIEL CORP.
MAMARONECK. NEW YORK

MSR-9 FINAL ASSEMBLY

DRAWN	CHECKED	FINAL APPROVAL
JS 10-2-64 ENG COORD	L. Gabel 10-2-64	RTC
		A3290 A

ELEC. DES. APP. | MECH. DES. APP.

TMC FORM 108-A

STOCK NO. 440H