| REQ. PER UNIT | USED ON MODEL | ASS'Y. NO. | DATE | | |
|---|---|---|---|---|---|
| 1 | LFCA-1 | A3892 | 4/15/65 | A3893 | Ø |

| SYMBOL(S) | ITEM NO. | USED TO MOUNT | QTY |
|---|---|---|---|
| | 2 | TF272 | 4 |
| | 3 | TX103 | 4 |
| | | 2N2143 | 2 |
| | 4 | TS166-1 | 6 |
| | 5 | TS166-1 | 6 |
| | 6 | TS166-1 | 6 |
| | 7 | TF272 | 4 |
| | 8 | TX103 | 4 |
| | | 2N2143 | 2 |
| T102 | 9 | | |
| XQ101-103 | 10 | | |
| Q102,103 | 11 | | |
| Q101 | 12 | | |

| REQ. | ITEM | PART NO. | DESCRIPTION | SYMBOL |
|---|---|---|---|---|
| 1 | 12 | 2N2143 | TRANSISTOR | |
| 1 | 11 | TX103 | TRANSISTOR | |
| 3 | 10 | TS166-1 | SOC,SCOND DEV | |
| 1 | 9 | TF272 | XFMR,AF | |
| 6 | 8 | SCBP0632BN8 | SCR,MACH | |
| 4 | 7 | SCBP0440BN4 | SCR,MACH | |
| 6 | 6 | SCBP0256BN6 | SCR,MACH | |
| 6 | 5 | NTH0256BN6 | NUT,PLN,HEX | |
| 6 | 4 | LWS02MRN | WASH.,LK,SPLIT | |
| 6 | 3 | LWE06MRN | WASH.,LK,EXT | |
| 4 | 2 | LWE04MRN | WASH.,LK,EXT | |
| 1 | 1 | LD1571/MS3937 | CHAS.,AF | |

| SYM | DESCRIPTION | DATE | CH. NO. | DRAFTS | CHECKER | ENG. APP. |
|---|---|---|---|---|---|---|
| Ø | ORIGINAL RELEASE FOR | 4-29-65 | | OJL | | |

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES: DECIMALS .X ± .05, .XX ± .01, .XXX ± .005; FRACTIONS ± 1/64; ANGLES ± 0° 30′

SCALE

CODE

STOCK SIZE

MATERIAL

TYPE & TEMPER | HEAT TREAT. SPEC.

FINISH & SPEC. NO.

POSE

THE TECHNICAL MATERIEL CORP.
MAMARONECK, NEW YORK

CHASSIS ASSEMBLY,AF

| DRAWN | CHECKED | FINAL APPROVAL |
|---|---|---|
| 4-27-65 ENG COORD | L. gabel 4-27-65 | M M Kay 5/4/65 |
| ELEC. DES. APP. | MECH. DES. APP. | A3893 Ø |

TMC FORM 108-A

REPROVEL NO. 440H 23845