" TEST	"Q"	EXT.CAP.	SYMBOL	INDUCTANCE 10KC BRIDGE		\langle		REVISIONS					
FREQ.	MIN.						SYM		DESCRIPTION		DATE E.M.N. NO. DRAFT		
		METĚR				\mathfrak{m}	×	EXPE		3.15.4		4	
6.5 MC	90	-#-		4.9 Mh ± .2 Mh	_		Ø	QRIGI	INAL RELEASE FOR PRO	The second secon	and the second s		
						(J)	A	CHG'D	'Q' MIN FR 105 .	9.25.6	6 16795 RME	W/a M	
		WINDING	DD COEDIDE			0	İ			·		-	
		WINDING	PROCEDURE			$ \omega $							
			ITEM 2 ON ITEM 1, STA			1	i						
2. SECONDARY - WIND 7 TURNS OF ITEM 6 OVER PRIMARY AND IN THE SAME DIRECTION STAKE WITH ITEM 3.						1							
			EAK OUT FROM OPPOSI	TE SIDE OF PRIM	ARY.	1 ~							
4. BAK	E COIL E	OR 15 MIN. AT	150°F, REMOVE FROM			L				·····	······································		
		TERMINALS ON B									,P/O IT	rem #1	
			THIN 1/4" OF COIL. IN BASE, TAKING CARE	TO POSITION NO	TCHES ON RAISED		İ					,, <u>.</u>	
7. PLACE ITEM 1 OVER SLUG ON BASE, TAKING CARE TO POSITION NOTCHES ON RAISED PART OF BASE.										P _		LELLY.	
8. SOLDER ALL LEADS TO PROPER COLOR-CODED TERMINALS ON BASE.							START START BLUE YELLOW						
9. ASSEMBLE AS PER ASSEMBLY DRAWING, PLACE IN CASE; BEND THE 4 TABS DOWN IN THE NOTCHES.						i							
10. DO NOT CUT OFF THE TWO LONG TABS.							PRIMARY) SECONDARY						
11. DELETED.							PRIMARY SECONDARY						
12. STAMP TMC PART NO. AS SHOWN 13. TEST INDUCTANCE, AND Q AS SHOWN ABOVE. SET INDUCTANCE FIRST.							RED GREEN WIRING DETAIL						
14. BAKE COMPLETED ASSEMBLY FOR ONE HOUR AT 212°F.							END END						
15. REMOVE COMPLETED ASSEMBLY FROM OVEN AND ALLOW TO COOL TO ROOM TEMPERATURE 16. REPEAT STEP NO. 13.							SCHEMATIC DIAGRAM						
			C UNIVERSAL BRIDGE.	'INDICTANCE ON	LV \		3	CHENIA	TIC DIAGRAPI	-			
			OIL TO REACH THE IND								. 5		
19. TES	T COIL	WITH "Q" METER	260A (FOR "Q" ONLY).	i.			ł					_	
			S SHOWN ABOVE. AND S									٠.۶٠	
21. IUN	E INE I	DUCIANCE DIAL	TO REACH THE MAX.	READING ON THE	WEIER.				*				
			•						,		•	•	
			3 1				×		WI-141-32-5	WIRE ELECTRIC			
							$\frac{\hat{x}}{x}$	5	BS-100	SOLDER, SOFT	AL		
	· · · · · · · · · · · · · · · · · · ·						<u> </u>	1	GL-130	ADHESIVE, Q-DOPE			
		G CORE			TSTAMP THE PART		X	4			41 41	* /	
	GRADE Re		CF135-8,	P/O ITEM #1	GOTHIC AS SHO		X	3	GL-103	ADHESIVE, N-CEL	<u></u>		
			_ \	-	1		X	 	WI - 104 - 3/43	WIRE, ELECTRICAL, L			
	YELLOW		── □【∪ - >	[لہ ۱	TT244		#-	#		-#	A Company		
				I C "I	1 / 3 1						1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		
		F 65		2			1	1 ITEM	CI-136- 2.	CORE, ADJUSTABLE TU		SYMBO	

