





- 1. INSERT EASTMAN 910 INTO OPENING OF ITEM 2.
- 2. INSERT ITEM 2 ON MOTOR SHAFT.
- 3. SCREW DOWN SET SCREW TO FLAT ON MOTOR SHAFT.

4. GRIND SET SCREW FLUSH TO ITEM 7

			/ /	EM	2.				
	×	4	EAST. 910		EASTMAN, ADHESIVE				
	/	3	SL4C0440	SP3 SCREW, ALLEN					
	1	2	PM 1498		SHAFT				
	1 1 MO-1				MOTOR	, RE	EVERSI	BLE	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED	REQ'D	ITEM	PART NUMBE	R	DESCRIPTION			SYM	
OR PLATED FINISHES DECIMALS FRACTIONS	F. BUDETTI LIST OF MATERIAL							<u> </u>	
.X ± .05 TOLS. 1/64 .XX ± .01 ANGLES .XXX ± .005 0° .30'	FINAL A	PPROV	B 8/36/1	THE TECHNICAL MATERIEL CORP.					
MATERIAL	MECH. E	DES.	UR SES		М	AMARO	NECK, NEW	YORK	
FINISH	ELEC	* 3*	1-30-7						
	CHECKED DATE			MOTOR, ASSY.					
	DRAWN GE BIST								
NOTICE TO PERSONS RECEIVING THIS DRAWING THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is					CODE IDEN				ISSUE
					82679	1 248		1890	D
								SHEET	OF