



ELECTRICAL SPECIFICATIONS:

COIL Latch relay - 1100 ohm ± 10%  
 Unlatch relay - 1500 ohm ± 10%  
 Both coils moisture resistant varnished

PILE UP 4 Forms C (4 P.D.T.)

CONTACTS Code 14, 1/4" silver  
 Rated 20 amperes 125V AC Resistive

ADJUSTMENT Latch - operate 220 V 60 cycles AC or less  
 Unlatch - operate - .025 amperes  
 Non - operate - .023 amperes

MOUNTING DATA:

Four 5/32" diameter holes on 1-1/2" X 1-1/4" mounting centers.

NOTE:  
 PHYSICAL APPEARANCE OF RELAYS WILL VARY DEPENDING ON VENDORS CONFIGURATION  
 IN ALL CASE'S ASSY WILL BE ELECTRICALLY & MECHANICALLY INTERCHANGEABLE

ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
B		NOTE ADD.	10-17-85			CPL	
A	1	CLERICAL CHANGE	9.2.64	4		bb @	

TOLERANCES: DEC. DIM. ±, FRAC. DIM. ±, ANGULAR DIM. ±

SCALE: MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES

1	GPT-DK	AR-161	A 5852	8-24-64
REQ. PER UNIT	MODEL	PROJECT NO.	ASS'Y. NO.	DATE
USED ON				

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
		PA SCREEN OVLD RELAY ASS'Y.	
		MATERIAL	
		TYPE & TEMPER	HEAT TREAT. SPEC.
		FINISH & SPEC. NO.	
		ELEC. DES. APP.	MECH. DES. APP.
		AR-108 B	