

REQ. PER UNIT		USED ON	
1	VLRA-1/AX433	ASSY. NO.	AX433
DATE		DATE	
1/7/65		1/7/65	

SYMBOL(S)	ITEM NO.	USED TO MOUNT	QTY
A1	1	A3211-5 to A3410	4
	6	CU102-3(CA792)	1
	7	A3211-5 to A3410	4
		A3410 to A3370	2
	8	CU102-3(CA792)	1
		TE104-2 WRG (A3370)	1
	9	A3410 to A3370	2
	10	A3211-5 to A3410	4
	11	CU102-3(CA792)	1

- 1 11 SCFP0632BN7 SCREW, MACHINE
- 4 10 SCBP0632BN8 SCREW, MACHINE
- 2 9 SCBP0632BN5 SCREW, MACHINE
- 1 8 PX100-1-186 INSULATION SLEEVING, SZ 5
- 7 7 LWF06MRN WASHER, LOCK, EXTERNAL
- 5 6 FW06HBN WASHER, FLAT
- 1 5 CA792 WIRING HARNESS, BRANCHED
- 4 4 BS100 SOLDER, TIN ALLOY
- 1 3 A3410 CHASSIS ASSEMBLY, CAPACITOR
- 1 2 A3370 CHASSIS ASSEMBLY, TRANSFORMER
- 1 1 A3211-5 PC BOARD, FINAL ASSEMBLY

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
		POSE	
THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK			
AX433 FINAL ASSY			
STOCK SIZE			
MATERIAL			
TYPE & TEMPER	HEAT TREAT. SPEC.	CHECKED	ENG. APP.
		1-19-65	L. Gohel
		1-19-65	1-19-65
FINISH & SPEC. NO.		MECH. DES. APP.	
			AX433

ORIGINAL RELEASE FOR PRODUCTION

DATE: 1-19-65

CHECKER: [Signature]

SCALE: [Blank]

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES: DECIMALS ±.05, FRACTIONS ± 1/64, ANGLES ± 0° 30'