REQ. PER UNIT	USED ON MODEL	ASS'Y. NO.	DATE	AX625	A
1	AX625		2-23-66		

SYMBOL(S)	ITEM NO.	USED TO MOUNT	QTY
J1	2		1
S1	3		1
TB1	4		1
	5	TM102-8	1
	6	TM102-8	2
	7	TM102-8	4
	8	TM102-8	4
	9	TM102-8	4
	11	SW105	1

REQ.	ITEM	PART NO.	DESCRIPTION
1	11	MP102-4	KNOB
1	10	CA 1227	WRG HARN,BRCHD
4	9	NTH0440BN6	NUT,PLN,HEX
4	8	LWE04MRN	WASH.,LK,EXT
4	7	SCBP0440BN12	SCR,MACH
2	6	MS154-1	PL,MTG,TERM.BD
1	5	PX336-8	INS, TERM.BD
1	4	TM102-8	TERM.BD-BARR
1	3	SW105	SW,ROTARY
1	2	JJ133-3	CONN,RECP,FML
1	1	LD2057/MS4883	PNL,FRONT

SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
A	ADDED IT. 11, QTY 1, MP102-4 KNOB, & IT. 11, SW105, QTY 1	7-22-66	16557	RME	JCB	AA
Ø	ORIGINAL RELEASE FOR PRODUCTION	2-24-66	—	JC	JCB	JDe

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES
DECIMALS .X ±.05, .XX ± .01, .XXX ±.005
FRACTIONS ± 1/64
ANGLES ± 0° 30'

SCALE

CODE

STOCK SIZE

MATERIAL

TYPE & TEMPER | HEAT TREAT. SPEC.

FINISH & SPEC. NO.

STURMER

THE TECHNICAL MATERIEL CORP.
MAMARONECK. NEW YORK

TRANSMIT MODE SELECTOR

DRAWN	CHECKED	FINAL APPROVAL
2-23-66	JCB	

ELEC. DES. APP.	MECH. DES. APP.	SYMBOL
M/L HS		AX625 A

TMC FORM 106-A

REPROVEL NO. 440H 23845