

CA1010 A

REVISIONS					
SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD APPD
Ø	ORIGINAL RELEASE FOR PRODUCTION	2-16-66	-M	JC	
A	INCREASED LENGTH 1T. 6, 2"	6/15/66	16405	JL	QCB

SYMBOL - DENOTES

○ = ITEM No's

⬡ = LUGS


□ = WIRE MARKERS

THIS SYMBOL DENOTES END OF INSULATION AND NAIL DRIVING POINT. WIRE MUST BE STRIPPED 3/4" BEYOND THIS POINT AND TINNED 1/2" UNLESS OTHERWISE SPECIFIED.

UNLESS OTHERWISE SPECIFIED WIRES SHOULD BE PLACED IN CABLE IN NUMERICAL SEQUENCE AS THEY APPEAR IN ITEM COLUMN BY CATEGORY.

- ALL R.F. CABLES
- ALL SHIELDED CABLES
- ALL OTHERS

SPACE LACING APPROXIMATELY 3/4" APART.



NOTES

1	GPT-10KLF	
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE 1:1	CODE A	

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
X	12	BS100	SOLDER, TIN ALLOY	
X	11	CD101-1-MW	CORD, NYLON, LACING	BLACK
8	10	LA101	BAND, MARKER, CBL	
8	9	TE120-2	TERM, LUG, SPADE	
	8	HWC16(19)U2	WIRE, ELECT, INS.	RED
	7	MWC18(16)U5		GREEN
	6	HWC16(19)U9		WHITE
	5	HWC18(16)U92		WH/RED
	4	MWC20(20)U2		RED
	3	MWC18(16)U9		WHITE
	2	MWC18(16)U97		VIOLET
	1	HWC18(16)U5	WIRE, ELECT, INS.	BLUE

F. BUDETTI LIST OF MATERIAL

MATERIAL: _____

FINISH: _____

TITLE: CABLE, ASSEMBLY (AR-173) TUNE-OPERATE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

DRAWN: [Signature]	DATE: 12-1-65	FINAL APPROVAL: [Signature]	DATE: 2/14/66
CHECKED: [Signature]	DATE: 2-15-66		
ELECT. DES. [Signature]	DATE:		
MECH. DES. [Signature]	DATE:		

DECIMALS: .X ± .05, .XX ± .01, .XXX ± .005

FRACTIONS: ± 1/64, ± 0° 30'

TOLERANCES

CA1010 A

M/L [Signature] 2/16

SHEET [] REV. LTR. []