

REVISIONS					
SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD APPD
Ø	ORIGINAL RELEASE FOR PRODUCTION	2-16-66	M	Jc	
A	INCREASED LENGTH 17.53 & 4 1"	6/5/66	16405	JL	JLB [Signature]

SYMBOL - DENOTES

○ = ITEM NO'S

⬡ = LUGS


□ = WIRE MARKERS

THIS SYMBOL DENOTES END OF INSULATION AND NAIL DRIVING POINT. WIRE MUST BE STRIPPED 3/4" BEYOND THIS POINT AND TINNED 1/2" UNLESS OTHERWISE SPECIFIED.

UNLESS OTHERWISE SPECIFIED WIRES SHOULD BE PLACED IN CABLE IN NUMERICAL SEQUENCE AS THEY APPEAR IN ITEM COLUMN BY CATEGORY.

- ALL R.F. CABLES
- ALL SHIELDED CABLES
- ALL OTHERS

SPACE LACING APPROXIMATELY 3/4" APART.



NOTES

1	GPT-10KLF	
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE 1/1	CODE A	

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
X	14	BS 100	SOLDER, TIN, ALLOY	
X	13	CD 101-1-MW	CORD, NYLON, LACING	BLACK
10	12	LA 101	BAND, MARKER, CBL	
10	11	TE 120-2	TERM, LUG, SPADE	
	10	MWC 20 (7) U0	WIRE, ELECT, INS.	BLACK
	9	U90		WH/BLK
	8	U6		BLUE
	7	U96		WH/BLU
	6	U91		WH/BRN
	5	U1		BROWN
	4	U6		BLUE
	3	U2		RED
	2	U4		YELLOW
	1	MWC 20 (7) U94	WIRE, ELECT, INS.	WH/YEL

F. BUDETTI LIST OF MATERIAL

MATERIAL: _____

FINISH: _____

TITLE: CABLE, ASSEMBLY (AR-172) IPA PLATE OVLD

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

DECIMALS: .X ± .05, .XX ± .01, .XXX ± .005

FRACTIONS: ± 1/64, ANGLES: ± 0° 30'

TOLERANCES

DRAWN: [Signature] DATE: 12-1-65

CHECKED: [Signature] DATE: 2-15-66

ELECT. DES. DATE: _____

MECH. DES. DATE: _____

FINAL APPROVAL: [Signature] DATE: 2/16/66

SHEET: CA1011

REV. LTR. A