



NOTE: USE SLEEVING (ITEM 21) FOR ALL PIN CONNECTIONS.

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
26	MWC 18 (16) U9	CABLE, INSULATED	WHITE
25	PL-192	CONNECTOR, PLUG R.F.	PI01, PI02
24	TE-156-32953	SOLDERLESS TERMINAL	
23	TE-120-2	SPADE LUG	
22	WL-103-6	SHIELD, FLEXIBLE	
21	PX-100-1-.106	INSULATED SLEEVING	
20	CD-101-1-MW	CORD LACING	
19	MS 3102A16S-15	CONNECTOR, RECEPTACLE	J101
18	MWC 18 (16) U0	CABLE, INSULATED	BLACK
17	6		BLUE
16	4		YELLOW
15	97		WH/PURPLE
14	3		ORANGE
13	7		PURPLE
12	95		WH/BRN.
11	1		BROWN
10	96		WH/BLUE
9	92		WH/RED
8	2		RED
7	5		GREEN
6	8		GREY
5	92		WH/RED
4	91		WH/BRN
3	MWC 18 (16) U 91	CABLE, INSULATED	WH/BRN
2	RG-58/U	CABLE, RF COAXIAL	
1	RG-58/U	CABLE, RF COAXIAL	

NOTICE TO PERSONS RECEIVING THIS DRAWING

THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.

Property of:  
THE TECHNICAL MATERIEL CORPORATION  
MAMARONECK, NEW YORK

ISSUE	ZONE	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
B	23	Item 23 SHORTEN 2"	7-24-61	5312	R.V.	R.V.	
C	2	ITEM 22 WAS PX 100-1-.106					
A		ITEM 5 WAS MWC 18 (16) U 91					
		ITEM 6 ADDED					
		ITEM 26 ADDED					

DEC. DIM. ±	FRAC. DIM. ±	ANGULAR DIM. ±	TOLERANCES	SCALE:
				MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES

REQ. PER UNIT	MODEL	SECTION	ASBY. NO.	DATE
1	ACU			10-3-60

THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK			
STOCK SIZE			
MATERIAL			
TYPE & TEMPER			
HEAT TREAT. SPEC.			
FINISH & SPEC. NO.			
DRAWN		ELEC. DES. APP.	
CHECKED		FINAL APPROVAL	
		CA-567	

CA-567 B

A

B

C

D

E

F

G

11

10

9

8

7

6

5

4

3

2

1

11

10

9

8

7

6

5

4

3

2

1