



5	SHIELD ITEM 5	ITEM 6 TO PIN C	ITEM 14	GND
7	SHIELD ITEM 7	ITEM 8 TO PIN E	ITEM 14	GND
7	YEL. OF ITEM 7	ITEM 8 PIN G	CAP. FEED THRU	
6	WH~BROWN	↑ ↑ ↑ D	FEED THRU	PIN 3 V301 V303
5	WH~ITEM 5		F FEED THRU	V302 PIN 8
4	BLACK		E GROUND SIDE OF C310 - R305	GND
3	WH~RED		C CAP FEED THRU	C322
2	BROWN	↓ ↓ ↓ A	CAP. FEED THRU	C323
1	RED	ITEM 8 TO PIN B	CAP. FEED THRU	C321
ITEM	COLOR	FROM ITEM 8	TO	SYM

1	14	TE-141-1	GROUND LUG	
X	13	BS-100	SOLDER, SOFT	
	12	PX-100-1-.208	INSULATION SLEEVING	
1	11	MS-3420-6A	SLEEVING	
1	10	MS-3420-8A	SLEEVING	
1	9	MS-3057-8	CLAMP, CABLE	
1	8	MS-3106B-16S-1P	CONNECTOR	
	7	MWCZZ(7)S-4	CABLE, SHIELD FLEX	YELLOW
	6	MWC-22(7)U 91	CABLE, INSULATED	WH/BRN
	5	MWCZZ(7)S 9	CABLE, SHIELD FLEX	WHITE
	4	MWC-22(7)U 0	CABLE INSULATED	BLACK
	3	↑ 92	↑ ↑	WH~RED
	2	↓ 1	↓ ↓	BROWN
	1	MWC-22(7) 2	CABLE INSULATED	RED
REQ. ITEM		PART NO.	DESCRIPTION	SYMBOL

C	PIGTAILS ADDED IT 5 & 7 ON PICT	10-24-60	17085	WHD	CRJ	
B 1	DWG NO WAS CA-534 (ERROR)	9/22/60	3066	WF	WLD	
A	TE-141-1 ADDED BUILDUP CLARIFIED	5/4/60			CRJ	
ISSUE ZONE	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
TOLERANCES		SCALE:				
DEC. DIM. ±		MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES				
FRAC. DIM. ±						
ANGULAR DIM. ±						

1	CMD-1	AO-103		3-25-60
REQ PER UNIT	MODEL	SECTION	ASS'Y. NO.	DATE

THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK			
CABLE, CONTROLLED M.O.			
STOCK SIZE			
MATERIAL			
TYPE & TEMPER		10B1160 U.R.P. WLD	
HEAT TREAT. SPEC.		DRAWN	ELEC. DES. APP.
FINISH & SPEC. NO.		CHECKED	FINAL APPROVAL
		CA-568 C	