



CA-766
0

REVISIONS

SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD	APPD
A	REDRAWN & REVISED					
0	ORIGINAL RELEASE FOR PRODUCTION	4-24-64		SRG		

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
	11	BS-100	SOLDER, SOFT	
	10	CD-101-1-MW	CORD LACING	BLACK
	9	LA-101-21 THRU 27	WIRE MARKER	
7	8	TE-120-2	LUG, SPADE	
	7	MWC 20(7) B 97	CABLE, INSULATED, FIBERGLASS	WH/VIO
	6	94		WH/YEL
	5	93		WH/ORN
	4	6		BLUE
	3	4		YELLOW
	2	MWC 20(7) B 93		WH/ORN
	1	MWC 18(16) B 96	CABLE, INSULATED, FIBERGLASS	WH/BLUE

THIS SYMBOL DENOTES END OF INSULATION & NAIL DRIVING POINT. WIRE MUST BE STRIPPED 3/4" BEYOND THIS POINT & TINNED 1/2" UNLESS OTHERWISE SPECIFIED.

WIRES SHOULD BE PLACED IN CABLE IN NUMERICAL SEQUENCE AS THEY APPEAR IN ITEM COLUMN. SPACE LACING APPROX. 3/4" APART.

~SYMBOL NOTES~

- DENOTES ITEM NOS.
- DENOTES LUGS
- DENOTES TAGS

1	GPT-200K	AR-148
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE	CODE	
	A	

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

F. BUDETTI

LIST OF MATERIAL

MATERIAL		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
FINISH		TITLE CABLE ASS'Y., GRID OVLD. RELAY JUMPER (RELAY B)	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	DRAWN W.A. FRANCO	DATE 4-23-63	FINAL APPROVAL <i>RDC</i>
	CHECKED <i>aa</i>	DATE	
DECIMALS .X ± .05 .XX ± .01 .XXX ± .005	TOLERANCES	ELECT. DES. <i>DBB</i>	DATE 4/13/64
FRACTIONS ± 1/64 ANGLES ± 0° 30'		MECH. DES. <i>J.D.</i>	DATE 2-7-64
		SHEET CA-766	
			REV. LTR. 0

NOTES