

CH-182

TUBE	TYPE	FUNCTION	SOCKET PIN NUMBERS								
			1	2	3	4	5	6	7	8	9
V1	12AU7	AVC AMP-RECT.	-0.6	-0.6	0.4	6.3*	6.3*	104	0	2.3	6.3*
V2	6BA6	I.F. AMP.	0	2.8	6.3*	6.3*	140	110	2.8		
V3	6BE6	1st MIXER	-11.2	2.2	6.3*	6.3*	280	75	0		
V4	6BE6	2nd MIXER	-4	0.7	6.3*	6.3*	170	42	0		
V5	12AT7	2nd OSC.-AUD. AMP.	134	-30	0	6.3*	6.3*	60	0	0.7	6.3*
V6	6AQ5	AUDIO OUT.	NC	19	6.3*	6.3*	300	300	0		
V7	6AG5	1st OSC.	-1.7	0.44	6.3*	6.3*	60	83	NC		
V8	6J6	REACT. MOD.	60	60	6.3*	6.3*	0	0	1.8		
V9	12AU7	RELAY DRIVER-SIDE TONE GEN.	60	0	1.4	6.3*	6.3*	148	30	58	6.3*
V10	5Y3	RECTIFIER	NC	365	NC	365*	NC	365*	NC	365	
V11	OA2	VOLT. REG.	150	NC	NC	NC	150	NC	0		

CONDITIONS:

ALL MEASUREMENTS TAKEN WITH V.T.V.M.

BFO - ON

SIDEBAND - MANUAL

NOISE LIMITER - OFF

AUDIO GAIN - CLOCKWISE

AVC - OFF

AVC - FAST

NO SIGNAL

NC = NO CONNECTION

* = AC VOLTAGE

AC LINE VOLTAGE - 115 V.

ALL VOLTAGES TO GROUND EXCEPT AC

FILAMENT VOLTAGES - ACROSS FILAMENTS

NOTICE TO PERSONS RECEIVING THIS DRAWING

THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.

Property of

THE TECHNICAL MATERIEL CORPORATION
MAMARONECK, NEW YORK

ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKED	ENG. APP.
TOLERANCES		SCALE:					
DEC. DIM. ±		MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION.					
FRAC. DIM. ±		REMOVE ALL BURRS AND SHARP EDGES					
ANGULAR DIM. ±							

MSR-6	PROJECT NO.	APPY. NO.	DATE
			8-20-60
REQ. PER UNIT	USED ON		

REV.	ITEM	PART NO.	DESCRIPTION	SYMBOL
			THE TECHNICAL MATERIEL CORP MAMARONECK, NEW YORK	
			VOLTAGE CHART	MODEL MSR-6
			MATERIAL	
			TYPE & TEMPER. HEAT TREAT. SPEC.	
			FINISH & SPEC. NO.	
			BLDG. DES. APP.	ISSN. DES. APP.
				CH-182