THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

REQ. PER UNIT	USED ON MODEL	ASS'Y. NO.	DATE
	HFR-1/N		7-6-62

CH-228

TUBE	TYPE	FUNCTION	SOCKET PIN NUMBERS 1	2	3	4	5	6	7	8	9
V1201	6BA6	IF AMP	0	1.1	6.3 VAC	0	175	92	1.1		
V1202	6BE6	IF GATE	0	*	6.3 VAC	0	180	82	0		
V1203	6BE6	IF GATE	0	*	6.3 VAC	0	180	82	0		
V1204	6AH6	GATE AMP	0	0	0	6.3 VAC	170	130	1.75		
V1205	6AH6	GATE AMP	0	0	6.3 VAC	0	170	135	1.75		

* DEPENDS ON SETTING OF R1210 BETWEEN 1.2 AND 2.1 VOLTS.

CONDITIONS:

ALL MEASUREMENTS TAKEN WITH VTVM.
NO INPUT SIGNALS.
ALL VOLTAGES ARE WITH RESPECT TO CHASSIS GROUND.
ALL VOLTAGES ARE D C UNLESS OTHERWISE NOTED.

REF: CK-557

SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES ON
FRAC. ± 1/64 DEC. ± .005 ANGLES ± 1/2°

SCALE:

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION.
REMOVE ALL BURRS AND SHARP EDGES

REQ.	ITEM	PART NO.	DESCRIPTION	SYMB L

STOCK SIZE

MATERIAL

TYPE & TEMPER | HEAT TREAT. SPEC.

FINISH & SPEC. NO.

THE TECHNICAL MATERIEL CORP.
MAMARONECK, NEW YORK

CHART, VOLTAGE
(MODEL HFR-1/N)

DRAWN	CHECKED	FINAL APPROVAL
R. Turchin	RUZZO	BP

ELEC. DES. APP.	MECH. DES. APP.	
		CH-228