THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

REQ. PER UNIT	USED ON MODEL	ASS'Y. NO.	DATE
	HFR-1/N		7-6-62

CH-231

TUBE	TYPE	FUNCTION	SOCKET PIN NUMBERS								
			1	2	3	4	5	6	7	8	9
V1201	6BA6	IF AMP	120K	68	FIL	0	6K	25K	68		
V1202	6BE6	IF GATE	47	*	FIL	0	6K	10K	1M		
V1203	6BE6	IF GATE	47	*	FIL	0	6K	10K	1M		
V1204	6AH6	GATE AMP.	1.5M	0	0	FIL	6K	25K	150		
V1205	6AH6	GATE AMP	580K	0	FIL	0	7K	25K	150		

* DEPENDS ON SETTING OF R1210. BETWEEN 100 AND 200 OHMS.

CONDITIONS:

ALL MEASUREMENTS TAKEN WITH OHMMETER, SIMPSON TYPE 260 OR EQUIVALENT.
ALL RESISTANCES ARE TO GROUND.
ALL POWER IS TURNED OFF.

K= ONE THOUSAND
M= ONE MILLION

REF: CK-557

SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.

UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN INCHES
TOLERANCES ON
FRAC. ± 1/64 DEC. ± .005 ANGLES ± 1/2°

SCALE:

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION.
REMOVE ALL BURRS AND SHARP EDGES

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL

STOCK SIZE

MATERIAL

TYPE & TEMPER | HEAT TREAT. SPEC.

FINISH & SPEC. NO.

THE TECHNICAL MATERIEL CORP.
MAMARONECK, NEW YORK

CHART, RESISTANCE
(MODEL HFR-1/N)

DRAWN	CHECKED	FINAL APPROVAL
R. Turchin	RUZZO	BP

ELEC. DES. APP.	MECH. DES. APP.	
		CH-231

TMC FORM NO. 108-A

DEFIANCE NO. 1020