



* CONNECT RI14 & RI15 TO V & W WHEN USING GROUNDED KEY LINES. THIS IS ONLY APPLICABLE WHEN TIS-3D IS IN CURRENT KEYED MODE.

CONNECT TO 230V TAP FOR 230V OPERATION

CONNECT TO 230V TAP FOR 230V OPERATION

SYMBOLS			
LAST		MISSING	
100SERIES	700SERIES	700SERIES	100 SERIES
C103	C708	V701	
CR109	CB704	V702	
J100	CR702	R704	
K101	E702		
Q100	F704		
RI15	J704		
S100 A,B	K703		
	L702		
	M701		
	R728		
	S703		
	T704		
	V708		

NOTE: (1) INCLUDES KIT 320 (SYMBOL NUMBERS IN THE '100 SERIES')
 (2) DIAGRAM SHOWN WITH JUMPERS "B" TO "C" (6 PLACES) FOR NEGATIVE GROUND KEYING LINE. FOR POSITIVE GROUND KEYING LINE, REMOVE "B" TO "C" JUMPERS AND JUMPERS "A" TO "B". (8 PLACES)

Δ	CONN. RI14 & RI15 NOTE ADDED	11/9/67	18610	HE	W	FB	de
⊗	ORIGINAL RELEASE FOR PRODUCTION	11/8/67		C.V.			
X	EXPERIMENTAL RELEASE	11-8-67		HE	W	FB	de

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES ON FRACTIONS ± 1/64 DECIMALS ± .005 ANGLES ± 1/2°

REQ. UNIT	PS4BI	MODEL	SECTION	ASSEMBLY NO.	DATE	11/8/67
USED ON						
FINISH & SPEC. NO.						
ELEC. DES. APP.						
MECH. DES. APP.						
SHEET						

CK1427

A

C

B

A

A