REQ. PER UNIT	USED ON MODEL	ASS'Y. NO.	DATE	CP70	C

STANDARD DRAWING

PART NO. SHALL BE AS SHOWN IN THE FOLLOWING EXAMPLE:

CP70	B	I	E	F	254	K
STYLE	TERMINAL	CIRCUIT	CHAR.	VOLT.	CAPACITANCE (UUF)	CAP. TOL.



CIRCUIT FOR CP70 WILL ALWAYS BE AS SHOWN.

NOTE:
FINISH & SPEC- ALL CAPACITORS SHALL BE PAINTED TMC GRAY (S115) OR EQUIVALENT.

NOTE: FOR MOUNTING BRACKETS, SEE CP07

FOR COMPLETE INFORMATION ON CP70, REFER TO MIL SPEC MIL-C-25A , MIL-C-25/7B & AMEND.

ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
C	1	PART NO. NOTE ADDED	3-25-63	8648			
B	1	FINISH & SPEC NOTE ADDED	11-7-62	7613			
A	–	REDRAWN NO REVISION	1/24/61	—			

TOLERANCES

DEC. DIM. ±
FRAC. DIM. ±
ANGULAR DIM. ±

SCALE:

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL

STOCK SIZE

MATERIAL

TYPE & TEMPER | HEAT TREAT. SPEC.

SEE NOTE

FINISH & SPEC. NO.

THE TECHNICAL MATERIEL CORP.
MAMARONECK. NEW YORK

CAPACITOR, FIXED, PAPER DIEL.

METAL CASE

DRAWN	CHECKED	FINAL APPROVAL
4/8/58		

ELEC. DES. APP. | MECH. DES. APP.

CP 70 C

FORM-108-A