IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES

STANDARD DRAWING

GL-10002 | A

USED ON			
MODEL	PROJECT NO.	ASS'Y. NO.	DATE

28/6/61

MATERIAL	NAME	SUPPLIERS
Resin	Laminac # 4116	Cyanamid of Canada.
Accelerator	Cobalt Napthenate 6%	1.) Nuodex Co., Toronto. 2.) W.C. Hardesty. 3.) O.P.W. Paints Limited
Filler	ASP-400	Superior Material, Inc. 120 Liberty ST. New York 6, N.Y.
Catalyst	1.) Laminac Catalyst # 347 2.) Lupersol: (60% Methyl Ethyl Ketone in Dimethyl Pthallate)	1.) Lucidol Division, Novadel-Agene Corp., 1740 Military Road, Buffalo 5, NY. 2.) J.H. Connor & Son Ltd., 207 Montcalm, Hull, P.Q.
Solvent	1.) Styrene thinners 2.) Laminac clean-up solvent # 3776	

NOTE: FOR PREPARATION SEE SPEC. S-10072

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL

STOCK SIZE

MATERIAL | WEIGHT PER PC.

TYPE & TEMPER

HEAT TREAT. SPEC.

FINISH & SPEC. NO.

TMC (Canada) LIMITED
OTTAWA ONTARIO

LAMINAC COLD POTTING

ISSUE	ITEM	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENG. APP.
A	1	UPDATED CHART	10/9/63	10164	[illegible]	[illegible]	[illegible]

DRAWN	ELEC. DES. APP.	MECH. DES. APP.
RWT/hh		[illegible]

CHECKED | FINAL APPROVAL

TOLERANCES		SCALE
ALL OTHERS	DEC DIM. ± FRAC. DIM. ± ANGULAR DIM. ±	DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED DRILL, PUNCH, COMMERCIAL STOCK SIZES AND MANUFACTURERS TOLERANCES ARE NOT INCLUDED.

GL-10002 | A

FORM — 127

IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES

STANDARD DRAWING

GL-10002

USED ON			
MODEL	PROJECT NO.	ASS'Y. NO.	DATE

28/6/61

MATERIAL	NAME	SUPPLIERS
Resin	Laminac # 4116	Cyanamid of Canada.
Accelerator	Cobalt Napthenate 6%	1.) Nuodex Co., Toronto. 2.) W.C. Hardesty. 3.) O.P.W. Paints Limited
Fillter	ASP-400	Alkali Co., Cleveland 14, Ohio.
Catalyst	1.) Laminac Catalyst # 347 2.) Lupersol: (60% Methyl Ethyl Ketone in Dimethyl Pthallate)	1.) Lucidol Division, Novadel-Agene Corp., 1740 Military Road, Buffalo 5, NY. 2.) J.H. Connor & Son Ltd., 207 Montcalm, Hull, P.Q.
Solvent	1.) Styrene thinners 2.) Laminac clean-up solvent # 3776	REVISED

OCT 8 1963

NOTE: FOR PREPARATION SEE SPEC. S-10072

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL

STOCK SIZE

MATERIAL | WEIGHT PER PC.

TYPE & TEMPER

HEAT TREAT. SPEC.

FINISH & SPEC. NO.

TMC (Canada) LIMITED
OTTAWA ONTARIO

LAMINAC COLD POTTING

ISSUE	ITEM	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENG. APP.

RWT/hh
DRAWN

ELEC. DES. APP.

MECH. DES. APP.

CHECKED

FINAL APPROVAL

GL-10002

TOLERANCES

ALL OTHERS
DEC. DIM. ±
FRAC. DIM. ±
ANGULAR DIM. ±

SCALE

DIMENSIONS IN INCHES UNLESS OTHERWISE PECIFIED

DRILL, PUNCH, COMMERCIAL STOCK SIZES AND MANUFACTURER TOLERANCES ARE NOT INCLUDED.

FORM — 127