

GL10006

ISSUE	ITEM	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENG. APP.	REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
Ø		REL. TO PROD.	29/6/67		A.P.							

1201 RTV primer is an air-drying silicone primer that improves the adhesion of RTV silicone rubber to various substrates. The primer is supplied as a dilute solution in acetone.

STORAGE OF THE PRIMER  
 After priming operation is completed, any remaining Silastic 1201 RTV primer should be returned to a sealable container as soon as possible for storage. The container should be kept tightly sealed when not in use. The primer evaporates rapidly when exposed to air.

TYPICAL PHYSICAL CHARACTERISTICS

- Colour ..... Straw
- Viscosity at 77 F, centipoises ..... Less than 1
- Specific Gravity ..... 0.82
- Flash Point ..... 5 F
- Solvent ..... Acetone
- Pounds per gallon ..... 6

WARNING

The solvent used in 1201 RTV primer is extremely flammable. It should be applied only in a well ventilated area, and kept away from heat, sparks and open flame.

The formulation may also be severely irritating to the eyes. In case of eye contact, flush with water for at least 15 minutes; obtain prompt medical attention.

**STANDARD DRAWING**

MODEL		PROJECT NO.	ASSY. NO.	DATE	STOCK SIZE		TMC (Canada) LIMITED OTTAWA ONTARIO	
MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES		IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.			MATERIAL		1201 RTV PRIMER	
TOLERANCES		SCALE			TYPE & TEMPER		DRAWN	
DEC. DIM. ±		DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED			HEAT TREAT. SPEC.		ELEC. DES. APP.	
FRAC. DIM. ±		DRILL, PUNCH, COMMERCIAL STOCK SIZES AND MANUFACTURERS TOLERANCES ARE NOT INCLUDED.			FINISH & SPEC. NO.		MECH. DES. APP.	
ANGULAR DIM. ±							FINAL APPROVAL	
ALL OTHERS							P A M	
							CHECKED	
							GIL0006	