

56 10007

ISSUE	ITEM	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENG. AP.	REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
Ø		REL. TO PROD	NOV 28/67		RPL	JW	JW					

  

**STANDARD DRAWING**

Rocol Core Locking Compound # 8, Extra "G"  
 Manufacturer S 10045 - 64

**NOTE:** If difficulty is experienced in applying a small amount of compound to finely threaded cores, heat the compound to about 100°C.  
 At this temperature it will melt, and have thinned out sufficiently to permit the proper amount to be applied and for the insides of the threads to be properly covered.

  

MODEL		PROJECT NO.	ASS'Y. NO.	DATE	NOV 28/67
<b>USED ON</b>					
MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION REMOVE ALL BURRS AND SHARP EDGES			IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.		
<b>TOLERANCES</b>					
ALL OTHERS	DEC. DIM. ±	FRAC. DIM. ±	ANGULAR DIM. ±		
DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED DRILL, PUNCH, COMMERCIAL STOCK SIZES AND MANUFACTURERS TOLERANCES ARE NOT INCLUDED.					
STOCK SIZE		MATERIAL	WEIGHT PER PC.	TMC (Canada) LIMITED OTTAWA ONTARIO	
		COMPOUND, CORE LOCKING			
TYPE & TEMPER		HEAT TREAT. SPEC.		FINISH & SPEC. NO.	
				Ø	
DRAWN		CHECKED		ELEC. DES. APP. MECH. DES. APP.	
JW				FINAL APPROVAL	
				GL 10007	