

IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES

SPECIFICATIONS:

Pouring Temp. 120° - 140° C
 Softening Point 90° C
 Flash Point 250° C
 Dielectric Strength 940 V. PER. MIL.

NOTE: SUPERCEDED GE # 229

GL-107

USED ON

MODEL PROJECT NO. ASSY. NO. DATE

KS-85-X J-227 8-20-53

REF: MINERALLAC INSULATING COMPOUND #78

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
		THE TECHNICAL MATERIEL CORP. MAMARONECK. NEW YORK	
STOCK SIZE		COMPOUND, INSULATING	#78
MATERIAL	WEIGHT PER PC.		
TYPE & TEMPER			
HEAT TREAT. SPEC.			
FINISH & SPEC. NO.			

DRAWN: JAD
 CHECKED: JAD
 ELEC. DES. APP. [Signature]
 MECH. DES. APP. [Signature]
 FINAL APPROVAL: GL-107

ISSUE ITEM	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENG. APP.
SCALE						
TOLERANCES						
DEC. DIM. ±	DRILL, PUNCH, COMMERCIAL STOCK SIZES AND MANUFACTURERS TOLERANCES ARE NOT INCLUDED.					
ALL OTHERS	FRAC. DIM. ±					
	ANGULAR DIM. ±					