

FREQ MC	VMO FREQ	DRIVER		POWER AMPLIFIER							
		BAND	TUNING	PA BAND	PA TUNING	PA LOADING	PA IG	PA IP	PA ISG	MODULATOR IP	ANTENNA CURRENT
2.0	2000	2-4		2-2.5							
2.5	2500	2-4		2-2.5							
2.5	2500	2-4		2.5-3							
3.0	3000	2-4		2.5-3							
3.0	3000	2-4		3.0-4							
4.0	4000	2-4		3.0-4							
4.0	2000	4-8		4-6							
6.0	3000	4-8		4-6							
6.0	3000	4-8		6-8							
8.0	2000	4-8		6-8							
8.0	4000	8-16		6-8							
8.0	4000	8-16		8-12							
10.0	2500	8-16		8-12							
12.0	3000	8-16		8-12							
12.0	3000	8-16		12-16							
14.0	3500	8-16		12-16							
16.0	4000	8-16		12-16							
16.0	2000	16-32		16-24							
16.0	2500	16-32		16-24							
20.0	2500	16-32		16-24							
22.0	2750	16-32		16-24							
24.0	3000	16-32		16-24							
24.0	3000	16-32		24-32							
26.0	3250	16-32		24-32							
28.0	3500	16-32		24-32							
30.0	3750	16-32		24-32							
32.0	4000	16-32		24-32							

NOTICE TO PERSONS RECEIVING THIS DRAWING

THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.

Property of:
THE TECHNICAL MATERIEL CORPORATION
MAMARONECK, NEW YORK

TEST CONDITIONS:
a. 50 OHM NON REACTIVE DUMMY LOAD.
b. POWER OUTPUT 750 WATTS
(3.9 AMPS AT 50 OHMS) MINIMUM
c. AUDIO TONE OF 1000 CYCLES
APPLIED TO AUDIO INPUT
TERMINALS OF RTM

REMARKS: _____
DATE : _____
MFGR NO. _____
SERIAL NO. _____
TESTED BY _____
APPROVED BY _____

MODEL-750 (B) 2
THE TECHNICAL MATERIEL CORP.
MAMARONECK NEW YORK

IN-1082

← 811 →

Dist