

LD-166

SHEET10F2

11/13/56

DATE

ASS'Y. NO.

170

PROJECT NO.

RSD-2

REQ. PER UNIT

HEAT TREAT. SPEC.

FINISH & SPEC. NO.

0 (+) 1 12AT7 12AT7 V3 12AX7 V 17 VI3 12AX7 12 A X 7 12 AU7 6C4 LETTERING TO BE 1/8" HIGH GOTHIC EXCEPT DANGER HIGH VOLTAGE WHICH IS TO BE 1/4" GOTHIC. SPACING BETWEEN LINES TO BE AS BELOW 0 V6____ 0 V5 6AL5 -19 VI5 6AL5 6AL5 0 TOP OF CHASSIS REAR OF CHASSIS RFG REF. DWG. A-515 REQ. ITEM PART NO. DESCRIPTION THE TECHNICAL MATERIEL CORP. MAMARONECK. NEW YORK STOCK SIZE CHASSIS LETTERING MATERIAL WEIGHT PER PO RSD-2 C.D.D. TYPE & TEMPER DRAWN ELEC. DES. APP. MECH. DES. APP.

FORM - 111

D 2 DIM. ADDED

OTHERS DEC. DIM. ± FRAC. DIM. ± 732

REDRAWN

CHANGED FROM TOLERANCES

111356 4 CDD PLX ATT

DATE CN. NO. DRAFTS CHECKER ENG. APP.

DRILL, PUNCH, COMMERCIAL STOCK

SIZES AND MANUFACTURERS

TOLERANCES ARE NOT INCLUDED.

IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETER-MINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES

