


- NOTES-
- 1- ALL ENGRAVING TO BE 3/32 HIGH WHITE GOTHIC UNLESS OTHERWISE SPECIFIED.
 - 2- ALL DOTS TO BE 3/32 DIA., WHITE FILLED.
 - 3- ALL LINES TO BE WHITE FILLED.
 - 4- ALL ENGRAVING TO BE CENTERED ON HOLES.
 - 5- ALL ARROW HEADS TO BE WHITE OUTLINE FILL

LETTER HEIGHT	DEPTH OF STROKE	WIDTH OF STROKE
3/32	.010	.015
1/8	.010	.020
LINES	.010	.015
ARROW HD.	.010	SEE DET.
DOTS	.010	SEE NOTE



NOTICE TO PERSONS RECEIVING THIS DRAWING

THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.

Property of:
THE TECHNICAL MATERIEL CORPORATION
MAMARONECK, NEW YORK

SYM	ZONE	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
B		ARROWHEADS CLARIFIED	5-1-62	6650	HS	MLA	BP
A		2 DOTS ADDED 82° OFFIC. ON TUNING DIAL	9-21-61	5596	HS	MLA	BP

UNLESS OTHERWISE SPECIFIED:

SCALE

DIMENSIONS ARE IN INCHES

TOLERANCES ON
FRACTIONS ± 1/64 DECIMALS ± .005 ANGLES ± 1/2°

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS & SHARP EDGES

REF: MS-2560 (8)

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK			
ENGRAVING, FRONT PANEL			
MATERIAL			
TYPE & TEMPER. HEAT TREAT. SPEC.			
FINISH & SPEC. NO.			
ELEC. DES. APP.		MECH. DES. APP.	

REQ. PER UNIT	MODEL	SECTION	ASSY. NO.	DATE
1	GPE-1			5-6-61

NO.	NAME	DATE	INITIALS
1	MLA	9/21/61	MLA
2	HS	5/1/62	HS

LD-916 B

LD-916 B