

REQ. PER UNIT	USED ON			LUI06	Ø
	MODEL	ASS'Y. NO.	DATE		
	GPT-40K				

**SPECIFICATIONS**

MATERIAL: LITHIUM TYPE GREASE  
 APPLICATIONS: GENERAL GREASING UNDER NORMAL CONDITIONS  
 AVERAGE WORKED PENETRATION: 315  
 NLGI NUMBER: ONE  
 MELTING POINT: +340°F (+171°C)  
 MINIMUM OPERATING TEMP: 0°F (-17.8°C)  
 WATER REPELLENT: YES  
 PSI: 25,000

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
	ONE POUND CAN	THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
	STOCK SIZE		
Ø	SEE SPECS.	GREASE, AIRCRAFT & INSTR.	
SYM	DESCRIPTION	DATE	CH. NO. DRAFTS CHECKER ENG. APP.
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		SCALE	
DECIMALS .X ± .05 .XX ± .01 .XXX ± .005	FRACTIONS ± 1/64 ANGLES ± 0° 30'	CODE A	S401-334 (630-AA)
TOLERANCES			
FINISH & SPEC. NO.		ELEC. DES. APP.	MECH. DES. APP.
		DRAWN JRB @ 10-28-64	CHECKED RAT
			FINAL APPROVAL LUI06 Ø