

APPLICATION

REVISIONS

QTY	MODEL USED ON STANDARD	ASS'Y NO.	LTR	DESCRIPTION	DATE	E.M.N.NO	DRAFT	CHKD	APPD
			D	COMPLETE REVISION	9/1/67	18392	C.V.	<i>My</i>	EFM

MFGR PART NO.: 39016

MFGR#(TMC CODE REF): S401-101

SPECIFICATIONS

1/4" TO 1/4" COUPLING

6-32 HARDENED STEEL SET SCREWS, 90° APART, (2)
IN EACH HUB

ANGULAR MISALIGNMENT: 10°

VOLTAGE RATING: 4400 VDC

TORQUE 10 INCH—LBS.

PURCHASING NOTE: VENDOR MUST INCLUDE THE FOLLOWING INFORMATION WHEN SHIPPING THIS ITEM TO TMC.

1. AN OUTLINE DRAWING OR ILLUSTRATION FROM CATALOG SHOWING ALL PERTINENT DIMENSIONS AND TOLERANCES.
2. ELECTRICAL AND/OR MECHANICAL SPECIFICATIONS AS SHOWN IN THEIR CATALOGS.

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
AND INCLUDE CHEMICALLY APPLIED
OR PLATED FINISHES

DECIMALS FRACTIONS
.X ± .05 1/64
.XX ± .01 TOLS. ANGLES
.XXX ± .005 0°-30°

MATERIAL

FINISH

REQ'D	ITEM	PART NUMBER	DESCRIPTION	SYM.
LIST OF MATERIAL				
FINAL APPROVAL	PAB		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
MECH. DES.				
ELECT. DES.				
CHECKED	CDD		COUPLING, FLEXIBLE, INSULATED	
DRAWN	JAD			
SIZE	A	CODE IDENT. NO.	DWG NO.	ISSUE
		82679	MC 111	D
SCALE			SHEET	OF

NOTICE TO PERSONS RECEIVING THIS DRAWING

THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from **THE TECHNICAL MATERIEL CORPORATION** to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.