IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.

MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES.

DIMENSIONS IN INCHES UNLESS OTHERWISE SPECIFIED

ISSUE	ITEM	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENG. APP.
Ø		REL TO PROD	APRL 1/68		AP		
A		DELE 4 "K" HOLES, CHG 4	8-1-78	21666	GDL		
B		4 "G" HOLES DELETED 4 L HOLES ADD	11-17-78	21747	GDL		
C		4 "F" HOLES DELETED	8-1-79		GDL		
D		H HOLES CHANGED 8-337 CSK	8-13-81		RAB	—	
E		CHANGED PANEL TO 1/8 DELETE 8 HOLES ADDED 2 CHAMFERS	10/96		RAB		

4 "K" HOLES DELETED

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
1	1	MS157-2H	PANEL, BLANK STANDARD	

THIS * HOLE DELETED ON MS10874-1

HOLE	DESCRIPTION	REQ'D
A	25/64 DIA.	1
B	SEE DETAIL	2
C	SEE DETAIL	4
D	1/2 DIA.	1
* E	3/8 DIA.	1
F	DELETED DIA.	4
G	11/64 DIA.	4
H	DRILL 13/64, CSK 82° TO .337	4
J	9/64 COUNTER BORE 1/8 DEEP	1
K	#47 DRILL (.078)	2
L	SEE DETAIL	4

MACHINING:

1. MILL ALL EDGES.
2. HOLES MUST BE DRILLED, UNLESS OTHERWISE SPECIFIED.
3. LATERAL BOW OF PANEL MUST BE KEPT TO .031 TOLERANCE.
4. PANEL MUST BE FREE OF ALL MACHINING MARKS, GOUGES AND SCRATCHES. IF NECESSARY, SAND FRONT OF PANEL WITH NO. 120 GRIT SANDPAPER.

MARK TMC P/NO. 1/8 HIGH GOTHIC ON REAR OF PANEL W LATEST REV. LETTER



(REF: MS157-2 BLANK PANEL)



DETAIL "L"



DETAIL "B"



DETAIL "C"

REF. LD10286

TOLERANCES			SCALE: 1:1
ALL OTHERS	DEC. DIM. ±	.X = .05	DRILL, PUNCH, COMMERCIAL STOCK SIZES AND MANUFACTURERS TOLERANCES ARE NOT INCLUDED.
	FRAC. DIM. ± 1/64	.XX = .01	
	ANGULAR DIM. ± 0° 30'	.XXX = .005	

AMC-21C		AX5251	MAY 8-1980
AX10047	070/68	A10692	FEB 16/68
MODEL	PROJECT NO.	ASS'Y. NO.	DATE
USED ON			

1/8 THK STOCK SIZE	TMC (Canada) LIMITED OTTAWA ONTARIO
ALUM 2024-T3 MATERIAL / WEIGHT PER PC.	PANEL, FRONT
TYPE & TEMPER	DRAWN: RPL; ELEC. DES. APP.; MECH. DES. APP.: XW
HEAT TREAT. SPEC.	CHECKED; FINAL APPROVAL
PRIME & PAINT TMC FINISH & SPEC. NO.	MS10874

FORM—129