



- A- 1/4 (.250) D. 4 REQ.
- B- 5/16 X 1/2 SLOTS 2 "
- C- 13/64 DIA. 1 "
- D- 1/2 X 1/2 SLOT 1 "

- UNLESS OTHERWISE SPECIFIED:
1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS.
 2. ALL ANGULAR BENDS 90°.
 3. REMOVE ALL BURRS AND SHARP EDGES.
 4. MOUNT INSERTS AFTER FINISHING.

MS-2269-H
METAL STAMP TMC PART NO.
1/8 HIGH, GOTHIC

NOTICE TO PERSONS USING THIS DRAWING
THE TECHNICAL MATERIAL CORP. claims proprietary right in this drawing and the use of this drawing for any purpose other than that for which it was prepared is prohibited without the written consent of THE TECHNICAL MATERIAL CORP. Any person who uses this drawing for any other purpose without the written consent of THE TECHNICAL MATERIAL CORP. shall be liable for all damages resulting therefrom.

THE TECHNICAL MATERIAL CORP.
MAMARONECK, NEW YORK

L	SLOTS AREA WAS PERFORATED	2-3-59	21876	GR			
H	A6 LINE REMOVED TO SHOW CORRECT CUT ON BOTTOM OF COVER	12/25/63	10633				
G	A2 BLANK SIZE REF: MS-1175-10, DELETED	4-25-63	8212				
F	E10 DIM. 17-1/8 +.000 WAS 17-1/4	11-9-62	7635				
ISSUE ZONE		DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.	
TOLERANCES		SCALE:					
DEC. DIM. ± 1/64		MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES					
ANGULAR DIM. ±							

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
.051		THE TECHNICAL MATERIAL CORP.	
STOCK SIZE		MAMARONECK, NEW YORK	
ALUMINUM		BOTTOM COVER	
MATERIAL			
5052-H32			
TYPE & TEMPER			
CHG-1			
5-10-60			
HEAT TREAT SPEC.			
S404 YELL. IRIDITE			
FINISH & SPEC. NO.			
REQ. PER UNIT	MODEL	SECTION	ASSY. NO.
			DATE
		USED ON	

MS-2269