



SPOTWELD ALL AROUND ON BOTH SIDES. (USE AS MANY SPOTWELDS AS PRACTICAL FOR MAXIMUM STRENGTH & DEPENDABILITY). REMOVE ALL SHARP CORNERS.

FINISH NOTE:  
 S 871 STEEL DEGREASING  
 3 1/4 ZINC CHROMATE PRIMER  
 3 1/5 SMOOTH GREY ENAMEL OR  
 PRIME & PAINT TO CUSTOMERS SPEC.

NOTICE TO PERSONS RECEIVING THIS DRAWING  
 THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed herein. This drawing is issued in confidence for engineering information only and may not be reproduced or used for manufacture without the written permission of THE TECHNICAL MATERIEL CORPORATION. If this drawing is used for manufacture assistance and is subject to recall at any time.  
 Property of:  
 THE TECHNICAL MATERIEL CORPORATION  
 MAMARONECK, NEW YORK

ISSUE NO.	DESCRIPTION	DATE	CHK. NO.	DESIGN	CHECKED	ENG. APP.

REQ. UNIT	REQ. NO.	MODEL.	SECTION	USED ON	APP. NO.	DATE
1		PTE-1				6-21-60

REQ. ITEM	PART NO.	DESCRIPTION	SYMBOL
26 GAUGE (.0179)		THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
STEEL			
COLD ROLLED			
TYPE B TENSAR			
HEAT TREAT SPEC.			
FINISH & SPEC. NO.			

REF: M5-1311 (8)  
 DRAWN BY: [Signature]  
 CHECKED BY: [Signature]  
 FINL. APPROVAL: [Signature]  
 M5-2309