



HOLES REQ'D

A ~ .166 DIA. 4

B ~ $\frac{.250}{.253}$ DIA. 2
 FOR (NT-129-1032-4)

NOTE:
 DIMENSIONS ARE IN INCHES.

MOUNT INSERTS IN (B) HOLES
 AFTER FINISHING.

FOR ALL PERSONS RECEIVING THIS DRAWING

THE TECHNICAL MATERIEL CORPORATION claims
 proprietary right in the material disclosed hereon.
 This drawing is issued in confidence for engineering
 information only and may not be reproduced or used
 to manufacture anything shown hereon without per-
 mission from THE TECHNICAL MATERIEL CORPORA-
 TION to the user. This drawing is loaned for mutual
 assistance and is subject to recall at any time.

Property of:
 THE TECHNICAL MATERIEL CORPORATION
 MAMARONECK, NEW YORK

A	1	.191 DIA TO $\frac{.250}{.253}$	NT-129-1032-4	3-20-61	4463	<i>add</i> C.G.	FOS
ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
TOLERANCES		SCALE: FULL					
DEC. DIM. $\pm .005$		MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION.					
FRAC. DIM. $\pm 1/64$		REMOVE ALL BURRS AND SHARP EDGES					
ANGULAR DIM. $\pm 1/2^\circ$							

1	DDRG E			3-15-61
REQ. PER UNIT	MODEL	PROJECT NO.	ASS'Y. NO.	DATE
USED ON				

2	1	NT-129-1032-4	NUT, ROUND, SWAGE TYPE	
REQ. ITEM	PART NO.		DESCRIPTION	SYMBOL
.064		THE TECHNICAL MATERIEL CORP.		
STOCK SIZE		MAMARONECK, NEW YORK		
ALUMINUM		BRACKET MOUNTING		
MATERIAL		(CAPACITOR ASSEMBLY)		
5052 H32		<i>add</i>	FOS	
TYPE & TEMPER		HEAT TREAT. SPEC.	DRAWN	CHECKED
S404 YELLOW IRIDITE		<i>add</i>	FINAL APPROVAL	
FINISH & SPEC. NO.		ELEC. DES. APP.	MECH. DES. APP.	MS-2540 A