



PERFORATED AREA
 .072 DIA. HOLES ON 1/8 CENTERS STAGGERED
 (IN LINE (REF.) (REF.)

MOUNT ITEMS 1 & 2
 IN ALL "A" HOLES
 AS SHOWN AFTER
 FINISHING

LEGEND		
HOLE	DESCRIPTION	REQ.
A	1/4 DIA.	6

METAL STAMP TMC PART NO.
 1/8 HIGH BLACK GOTHIC

USE MATERIAL THICKNESS FOR MAX. RADIUS
 ON ALL BENDS UNLESS OTHERWISE SPECIFIED

6	2	FS-109-3	RING, STUD RETAINING	A
6	1	FS-110-1	STUD, SLOTTED HEAD	A
REQ. ITEM		PART NO.	J. STRUMER DESCRIPTION	SYMBOL
		.051	THE TECHNICAL MATERIEL CORP.	
		STOCK SIZE	MAMARONECK, NEW YORK	
		ALUM. PERFI	COVER, TOP	
		MATERIAL		
		5052-H32	3/12/63	BP
		TYPE & TEMPER	DRAWN	CHECKED
		HEAT TREAT. SPEC.	D. Koshari	3-12-63
		S404 YEL. IRIDITE	MS-2940 C	
		FINISH & SPEC. NO.	ELEC. DES. APP.	MECH. DES. APP.
			SHEET OF	

C	B4	DIM. 1 3/4 ADDED -- PERFORATED AREA CHANGED TO STAGGERED HOLES	9-23-63	9981	G.D.L.		
B	B2	ITEM # (2) WAS FS-109	7-18-63	9568	Ap.		
A	B1	BLANK SIZE REF: MS-1775-17, DELETED	4-25-63	8912			
SYM	ZONE	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
UNLESS OTHERWISE SPECIFIED:			SCALE				
DIMENSIONS ARE IN INCHES			MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS & SHARP EDGES				
TOLERANCES ON							
FRACTIONS ± 1/64			DECIMALS ± .005		ANGLES ± 1/2°		

1	TRX-1			3-30-62
REQ. PER UNIT	MODEL	SECTION	ASS'Y. NO.	DATE