



MOUNT IN ALL "B" HOLES.

METAL STAMP TMC PART NO.  $\frac{1}{8}$  HIGH GOTHIC, MARK TMC PART NO. WITH LATEST REVISION LETTERS.

MS-3030 E

REVISIONS

SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD	APPD
C	REVISED & REDRAWN FROM MS-3030, SIZE 1	6-26-63	9282			
D	DWG NO MS-3030 WAS MS-3408	7-2-63	9385			
E	REVISED COMPLETELY	5.18.64	11377			

LEGEND		
HOLE	DESCRIPTION	REQ.
A	$\frac{11}{64}$ DIA.	4
B	$.191-.194$ DIA.	2

NOTES :

- UNLESS OTHERWISE SPECIFIED
- 1. USE MATERIAL THICKNESS FOR MAX. RADIUS ON ALL BENDS.
- 2. ALL BENDS 90°.
- 3. DEBURR ALL SHARP EDGES.
- 4. MOUNT INSERTS AFTER FINISHING.

REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
4	1	NT-129-632-4	NUT, ROUND, SWAGE TYPE	B

J. STRUMER LIST OF MATERIAL

MATERIAL	.064 THK 5052-H32 ALUMINUM	THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK
FINISH	S-404 YEL IRIDITE	TITLE
		BRACKET, MOUNTING, RECTIFIER CIRCUIT

1	GPR-92	
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE	CODE	
$\frac{1}{1}$		

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		DRAWN	DATE	FINAL APPROVAL	DATE
DECIMALS .X ± .05 .XX ± .01 .XXX ± .005		DATE	DATE	MS-3030	E
FRACTIONS ± 1/64 AN LES ± 0° 30'		DATE	DATE		
TOLERANCES		ELECT. DIA.	DATE	SHEET	REV. LTR.
		MECH. DIA.	DATE		