



① MOUNT IN ALL "A" HOLES

OPPOSITE SIDE IDENTICAL

MS4039 B

REVISIONS					
SYM	DESCRIPTION	DATE	E.M.N. NO.	DRAFT	CHKD APPD
X	EXPER. RELEASE	9-21-64	X		
Ø	ORIGINAL RELEASE FOR PRODUCTION	9-25-64	Ø	J.L.	
A	"B" WAS 3/16 X 1 SLOT, 2 "C" HOLES ADD, 5 5/32 WAS 4 7/8	10.9.64	12604	WB	MDP
B	1 1/32 WAS 1/32	10.26.64	12773	WB	MDP

HOLE	DESCRIPTION	REQ.
A	.191-.194 DIA	4
B	3/16 DIA	1
C	13/64 DIA	2

UNLESS OTHERWISE SPECIFIED:

1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS
2. ALL ANGULAR BENDS 90 DEGREES
3. REMOVE ALL BURRS AND SHARP EDGES
4. MOUNT INSERTS AFTER FINISHING

4	1	NT129-632-4	NUT, PLAIN SPLINE	A
REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
GELLMAN LIST OF MATERIAL				
MATERIAL			THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
.064 ALUMINUM 5052-H32			BRACKET, MOUNTING - RECORDER	
FINISH			TITLE	
5404 YELLOW IRIDITE			BRACKET, MOUNTING - RECORDER	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES				
DRAWN		DATE	FINAL APPROVAL	
E. Jensen		9-21-64	RT	
CHECKED		DATE	DATE	
J.P.S. @		9-25-64	MS4039	
ELECT. DES.		DATE	REV. LTR.	
MECH. DES.		DATE	B	
SHEET				

1	PFCB-1	
Q'TY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE	CODE	
1:2	A	

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

DECIMALS	TOLERANCES	FRACTIONS
.X ± .05		± 1/64
.XX ± .01		ANGLES
.XXX ± .005		± 0° 30'

NOTES