



REQ. PER UNIT	USED ON		MS4342 Ø
	MODEL	ASS'Y. NO.	
1	CPT-10K( )7		2-5-65

HOLES:  
 A-.191-.194 DIA. (2REQ.)  
 B-.250-.253 DIA (1REQ.)

METAL STAMP TMC PART NO.  
 1/8 HIGH GOTHIC W/LATEST  
 REV. LETTER.

UNLESS OTHERWISE SPECIFIED:

1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS
2. ALL ANGULAR BENDS 90 DEGREES
3. REMOVE ALL BURRS AND SHARP EDGES
4. MOUNT INSERTS AFTER FINISHING

1	2	NT129-1032-4	NUT, PLAIN, SPLINE	B
2	1	NT129-632-4	NUT, PLAIN, SPLINE	A
REQ. ITEM		PART NO.	F. BUDETTI DESCRIPTION	SYMBOL

Ø	ORIGINAL RELEASE	8-20-65	Ø	GDL			
X	EXP. RELEASE	2-5-65	X	SRG			
SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		SCALE		1:1			
DECIMALS	FRACTIONS	CODE					
.X ± .05	± 1/64	A					
.XX ± .01	ANGLES						
.XXX ± .005	± 0° 30'						

.081 THICK		THE TECHNICAL MATERIEL CORP.			
STOCK SIZE		MAMARONECK, NEW YORK			
ALUMINUM		BRACKET, SHIELD MTG.			
MATERIAL					
5052-H32		SRG	JCB	M/May 8/20/65	
TYPE & TEMPER	HEAT TREAT. SPEC.	DRAWN	CHECKED	FINAL APPROVAL	
S404 YEL, IRIDITE					
FINISH & SPEC. NO.	ELEC. DES. APP.	MECH. DES. APP.	MS4342 Ø		