



METAL STAMP TMC P/N,  
WITH LATEST REV. LETTER

REQ. PER UNIT	USED ON			MS 4579	∅
	MODEL	ASS'Y. NO.	DATE		
1	RGCB-1		5-6-65		

HOLE	DESCRIPTION	REQ.
A	11/64 DIA	2

UNLESS OTHERWISE SPECIFIED:

1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS
2. ALL ANGULAR BENDS 90 DEGREES
3. REMOVE ALL BURRS AND SHARP EDGES
4. MOUNT INSERTS AFTER FINISHING

REF: LD1899

							REQ. ITEM	PART NO.	F. EATON	DESCRIPTION	SYMBOL
								.062	THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK		
								STOCK SIZE	BRACKET, MOUNTING, RELAY		
∅	ORIGINAL RELEASE FOR PRODUCTION	5/7/65	#	Pl	J.M.			ALUMINUM			
SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.		MATERIAL			
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		SCALE					5052-H32		Pl	W. J. JORPAN	5/18/65
		1:1					TYPE & TEMPER	HEAT TREAT. SPEC.	DRAWN	CHECKED	FINAL APPROVAL
DECIMALS	TOLERANCES	FRACTIONS	CODE				5404 VEL. IRIDITE		W. J. JORPAN	5/14/65	MS4579
.X ± .05		± 1/64	A				FINISH & SPEC. NO.		ELEC. DES. APP.	MECH. DES. APP.	∅
.XX ± .01		ANGLES									
.XXX ± .005		± 0° 30'									