



MS 4659 A

REVISIONS					
SYM	DESCRIPTION	DATE	EM N NO	DRAFT	CHKD APPD
X1	COMPLETELY REVISED	7-1-65	X	MP	JC
Ø	ORIGINAL RELEASE FOR PRODUCTION	3-3-66	-A	JC	MP
A	SLOTS AREA WAS PERFORMED	9-21-83	22064	GDL	MP

HOLES:
A - .191-.194 DIA. (10 REQ.)

TMC P/N	X
MS 4659-1	1-3/8
MS 4659-2	2-3/4

MARK TMC PART NO.
1/8 HIGH GOTHIC W/LATEST
REV. LETTER

- UNLESS OTHERWISE SPECIFIED:**
- USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS
 - ALL ANGULAR BENDS 90 DEGREES
 - REMOVE ALL BURRS AND SHARP EDGES
 - MOUNT INSERTS AFTER FINISHING

NOTES

1 EA	TST () 10K	
QTY./UNIT	MODEL USED ON	ASS'Y. NO.
SCALE	CODE	
1:1	A	

THE CONTENTS OF THIS DRAWING ARE THE EXCLUSIVE PROPERTY OF THE TECHNICAL MATERIEL CORP. ITS UNAUTHORIZED USE OR REPRODUCTION IN WHOLE OR IN PART IS STRICTLY FORBIDDEN.

10	1	NT 129-632-4	NUT, PLAIN, SPLINE	
REQ'D.	ITEM	PART NUMBER	DESCRIPTION	SYMBOL
F. BUDETTI LIST OF MATERIAL				
MATERIAL			THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	
.051 THICK ALUMINUM 5052-H32			TITLE SHIELD, RF FIXED FILTER	
FINISH S245 COPPER FLASH S245 SILVER PLATE S423 IRIDITE 18-P SILVER KOTE			DRAWN MPH DATE 5-27-65 FINAL APPROVAL MPH DATE 3-2-66	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES			ELECT. DES. DATE 3-2-66	
DECIMALS .X ± .05 .XX ± .01 .XXX ± .005			MECH. DES. DATE 3-2-66	
FRACTIONS ± 1/64 ANGLES ± 0° 30'			SHEET MS 4659	
TOLERANCES			REV. LTR. A	

M/L