



HOLE	DESCRIPTION	REQ	REQ. PER UNIT	USED ON		
				MODEL	ASS'Y. NO.	DATE
A	13/64 DIA.	3	2	PSP-350B	A4445	3-15-66

MS4895 A

METAL STAMP TMC PART NO. 1/8 HIGH GOTHIC W/LATEST REV. LETTER

MS4895-1 - AS SHOWN
 MS4895-2 - OPPOSITE HAND

* THIS HOLE REQ ON MS4895-2
 MS4895-2 ONLY.

- UNLESS OTHERWISE SPECIFIED:
1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS
 2. ALL ANGULAR BENDS 90 DEGREES
 3. REMOVE ALL BURRS AND SHARP EDGES

REF: LD2063 FOR MS4895-1

REQ.	ITEM	PART NO.	DESCRIPTION				SYMBOL
		.064	THE TECHNICAL MATERIEL CORP.				
		STOCK SIZE	MAMARONECK, NEW YORK				
A	"A" HOLE ADDED	4-1-66 16049	WFW	QC			
	ORIGINAL RELEASE FOR PRODUCTION	3-16-66	WFW				
SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES		SCALE 1:1					
DECIMALS .X ± .05 .XX ± .01 .XXX ± .005	TOLERANCES	FRACTIONS ± 1/64 ANGLES ± 0° 30'	CODE A				
		5052-H32		H. AUSTIN	QC	Final Approval	
		TYPE & TEMPER	HEAT TREAT. SPEC.	DRAWN	CHECKED	FINAL APPROVAL	
		3404-YEL. IRIDITE		3-15-66			
		FINISH & SPEC. NO.	ELEC. DES. APP.	MECH. DES. APP.	MS4895 A		