



		REVISIONS					
E.M.N.O.	DRAFT	CHKD	ZONE	LTR	DESCRIPTION	DATE	APPROVED
					ORIGINAL RELEASE FOR PRODUCTION	5/15/71	P.E.A.
20607	GE	Q	A		CHG 8 D HOLES TO F HOLES	4/26/72	Q
21088	GE	Q	B		ADD 7 C HOLS & 2 AHLS 4 D HLS	5/26/73	Q
21097	GE	Q	C		4 H. HOLES WERE D HOLES	6/29/73	Q
	GE		D		UPDATED HOLE CHART	1/3/74	

HOLE DESCRIPTION	REQ.
A ~ 1/64 DIA.	7
B ~ .191-.194 DIA.	6
C ~ .221-.224 DIA.	20
D ~ .250-.254 DIA.	22
E ~ .344-.347 DIA.	8
F ~ DELETED	
G ~ 3/4 DIA.	2

MARK TMC PART NUMBER
1/8 HIGH GOTHIC WITH LATEST
REVISION LETTER

QTY. REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
8	4	NT129-420-6	NUT, RN, SWAGE	E
22	3	NT129-1032-6	" " "	D
20	2	NT129-0832-6	" " "	C
6	1	NT129-0632-6	" " "	B

BUDETTI LIST OF MATERIAL

FINAL APPROVAL	DATE
MECH. DES.	DATE
ELECT. DES.	DATE
CHECKED	DATE
DRAWN	DATE

THE TECHNICAL MATERIEL CORP.
MAMARONECK, NEW YORK

CHAS. POW. SUP.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	
TOLERANCES ON DECIMALS .X ± .05 .XX ± .01 .XXX ± .005	FRACTIONS ± 1/64 ANGLES ± 0° -30'
MATERIAL .125 ALUM 5052-H32	FINISH S404 YEL IRID

SIZE	CODE	IDENT NO.	DWG NO.	ISSUE
D	82679		MS 5944	0
SCALE				SHEET 1 OF 2

- UNLESS OTHERWISE SPECIFIED:
- USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS.
 - ALL ANGULAR BENDS 90 DEGREES.
 - REMOVE ALL BURRS AND SHARP EDGES.
 - MOUNT INSERTS AFTER FINISHING.

1	HFTA-1KJ	API52
QTY / UNIT	MODEL USED ON	ASS'Y NO.
APPLICATION		
CODE		
NOTICE TO PERSONS RECEIVING THIS DRAWING THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.		