



MS6785-1 AS SHOWN  
MS6785-2 WITHOUT DETAIL "D" & "E" HOLE

- UNLESS OTHERWISE SPECIFIED:
1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS.
  2. ALL ANGULAR BENDS 90 DEGREES.
  3. REMOVE ALL BURRS AND SHARP EDGES.
  4. MOUNT INSERTS AFTER FINISHING.

HOLES	DESCRIPTION	REQ'D
A	.191-.194 DIA	6
B	SEE DETAIL	4
C	9/64 DIA	4
D	3/16 DIA	14
E	7/16 DIA	1

QTY / UNIT	MODEL USED ON	ASS'Y NO.
1	AX 5221	RCMT-1
1	AX 5220	RCMT-1
APPLICATION		
CODE		

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES ON  
DECIMALS .X ± .05  
.XX ± .01  
.XXX ± .005

FRACTIONS ± 1/64  
ANGLES ± 0° - 30°

MATERIAL .063 THK ALY 5052-H32  
FINISH 8404 VEL IRIDITE

QTY. REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
10	1	NT 129 0632-4	NUT, ROUND	A
LIST OF MATERIAL				
<b>THE TECHNICAL MATERIEL CORP.</b> MAMARONECK, NEW YORK				
CHASSIS, MAIN				
FINAL APPROVAL	DATE			
MECH. DES.	DATE			
ELECT. DES.	DATE			
CHECKED	DATE			
DRAWN	DATE			
G.D.L.	3-17-77			
SIZE	CODE	IDENT NO.	DWG NO.	ISSUE
D	82679	MS 6785		X
SCALE 1:1			SHEET OF	

NOTICE TO PERSONS RECEIVING THIS DRAWING  
THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed herein. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown herein without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.