



UNLESS OTHERWISE SPECIFIED:

1. USE MATERIAL THICKNESS FOR MAXIMUM RADIUS ON ALL BENDS.
2. ALL ANGULAR BENDS 90 DEGREES.
3. REMOVE ALL BURRS AND SHARP EDGES.
4. MOUNT INSERTS AFTER FINISHING.

HOLES

A - 13/64 DIA	13 REQ'D
B - 11/64 DIA	12 REQ'D
C - 3/4 DIA	15 REQ'D
D - .221-.224 DIA	18 REQ'D
E - 9/32 DIA	4 REQ'D
F - 3/8 DIA	1 REQ'D
G - 9/64 DIA	6 REQ'D
H - 1/4 DIA	8 REQ'D
L - 1" DIA	4 REQ'D
M - 1/2 DIA	2 REQ'D

REF: LD

QTY. REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
18	1	NT129 0832-4	NUT, ROUND	D

LIST OF MATERIAL

THE TECHNICAL MATERIEL CORP.
MAMARONECK, NEW YORK

CHASSIS, PWR SUPPLY

FINAL APPROVAL	DATE
MECH. DES.	DATE
ELECT. DES.	DATE
CHECKED	DATE
DRAWN G.D.L	DATE 10-23-80

TOLERANCES ON

DECIMALS	FRACTIONS
.X ± .05	± 1/64
.XX ± .01	ANGLES
.XXX ± .005	± 0°-30'

MATERIAL .081 THK
ALUM 5052-H32

FINISH S404
YEL. IRIDITE

MODEL USED ON	ASSY NO.
APPLICATION	
CODE	

NOTICE TO PERSONS RECEIVING THIS DRAWING

THE TECHNICAL MATERIEL CORPORATION claims proprietary right in the material disclosed hereon. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without permission from THE TECHNICAL MATERIEL CORPORATION to the user. This drawing is loaned for mutual assistance and is subject to recall at any time.

SIZE	CODE IDENT NO.	DWG NO.	ISSUE
D	82679	MS 7048	
SCALE 1:1		SHEET	OF