STANDARD DRAWING

REQ. PER UNIT	USED ON MODEL	ASS'Y. NO.	DATE	NP788	Ø
	GPT10K GPT40K		8/11/65		

SYMBOL REF. DESIG.	SYMBOL REF. DESIG.
S905	S8103
S906	S8104
S1006	
S1007	
S1008	
S1009	
S1010	
S1011	
S7102	
S7103	
S7104	
S7303	
S7306	
S7501	
S8101	
S8102	

REFER TO CHART FOR APPROPRIATE SYMBOL REF. DESIG. MARKING 1/8 HIGH BLACK GOTHIC.



REMOVAL TAB FOR PROTECTIVE BACKING

SPECIFICATIONS:

1. BACKGROUND COLOR: ALUMINUM
2. LETTERING: 1/8 HIGH BLACK GOTHIC
3. BORDER: NONE
4. ADHESIVE: PRESSURE SENSITIVE ADHESIVE BACKING.
5. TO BE SUPPLIED IN STRIP FORM INDIVIDUALLY CUT.

TMC PART NO. TO BE IN FOLLOWING FORM
NP788 - S8104

BASIC PART NO. — SYMBOL REF. DESIG. SEE CHART

SYM	DESCRIPTION	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.
Ø	ORIGINAL RELEASE FOR PRODUCTION	8/13/65	Ø	R.V.V		

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES

TOLERANCES: DECIMALS .X ±.05, .XX ±.01, .XXX ±.005; FRACTIONS ± 1/64; ANGLES ± 0° 30′

SCALE

CODE

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL

STOCK SIZE

MATERIAL

TYPE & TEMPER | HEAT TREAT. SPEC.

FINISH & SPEC. NO.

THE TECHNICAL MATERIEL CORP.
MAMARONECK, NEW YORK

MARKER, IDENTIFICATION, ADHESIVE

DRAWN	CHECKED	FINAL APPROVAL
	J.De	M.M.Kay 8/13/65

ELEC. DES. APP. | MECH. DES. APP.: 8/13/65

NP788 Ø

TMC FORM 108-A

REPROVEL NO. 440H 21540