

IF IT IS FOUND DESIRABLE TO CHANGE ANY TOLERANCE OR OTHER DETAIL SPECIFIED ON THIS DRAWING NOTIFY THE PURCHASER PROMPTLY.

STANDARD DRAWING

PX-342 B


MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES

USED ON

MODEL PROJECT NO. ASS'Y. NO. DATE

TMC NO.	CAT. NO.	GUAGE SIZE	APPROX. I. D.
PX-342		20	.034
		18	.042
		16	.053
		14	.066
		12	.085
		10	.106
		8	.135
		6	.166
		4	.208
		2	.263
		1	.294

TYPE DESIGNATION TO BE IN FOLLOWING FORM.



SLEEVING - FIBERGLASS BRAID, COATED INSIDE AND OUTSIDE WITH VARNISH. AVER. DIELECTRIC STRENGTH - 5000 V. MAX. "HOTTEST SPOT" TEMP. - 130° C

COLOR	CODE
BLACK	0
BROWN	1
RED	2
ORANGE	3
YELLOW	4
GREEN	5
BLUE	6
WHITE	9

REF:

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL
			THE TECHNICAL MATERIEL CORP. MAMARONECK. NEW YORK	
		STOCK SIZE	INSULATION, SLEEVING	
		MATERIAL WEIGHT PER PC.	FIBERGLASS	
		TYPE & TEMPER	CDD	WOC
		HEAT TREAT. SPEC.	DRAWN JAD 7/19/56	ELEC. DES. APP. MECH. DES. APP. A.J.J.
		FINISH & SPEC. NO.	CHECKED	FINAL APPROVAL PX-342 B

B	1	ADDED ON CHART .294 I.D.	G-1763	9253	E	YAS	A.J.J.
A	1	DELETED CAT. No's ? REF. TO BIRN BACH -	4/8/58	1	WOC	file	A.J.J.
ISSUE	ITEM	CHANGED FROM	DATE	CN. NO.	DRAFTS	CHECKER	ENG. APP.

TOLERANCES

SCALE

ALL OTHERS
DEC. DIM. ±
FRAC. DIM. ±
ANGULAR DIM. ±

DRILL, PUNCH, COMMERCIAL STOCK SIZES AND MANUFACTURERS TOLERANCES ARE NOT INCLUDED.