



| | | | | | |
|----------------|---------|-----------|--------|--------|---|
| REQ. PER. UNIT | USED ON | | | RL-123 | C |
| | M DEL | ASS'Y. N. | DATE | | |
| 1 | GPT 10K | T 1-106 | 4-8-59 | | |

ELECTRICAL SPECIFICATION

COIL ~ LATCH RELAY ~ $1100 \Omega \pm 10\%$
 UNLATCH RELAY ~ $43 \Omega \pm 10\%$
 BOTH COILS MOISTURE RESISTANT
 VARNISHED.

PILE UP ~ 4 FORM C (4 P.D.T.)

CONTACTS ~ CODE 14 1/4" SILVER
 RATED 20 AMPERES 125V AC RESISTIVE

ADJUSTMENT ~ LATCH-OPERATE ~ $190V \pm 5\%$ 60 CYCLE AC OR LESS
 UNLATCH-OPERATE ~ .155 AMPERES
 NON-OPERATE ~ .140 AMPERES

NO LONGER AVAILIABLE
 REPLACE BY RL 202

| REQ. | ITEM | PART NO. | DESCRIPTION | SYMBOL | | | | | | | | | | | |
|----------------|------|--|------------------------------|--------------------|--------|-------------------|-----------|----------------|--|------------|--|----------------|--|--|--|
| C | | | THE TECHNICAL MATERIEL CORP. | | | | | | | | | | | | |
| B | 1 | | MAMARONECK, NEW YORK | | | | | | | | | | | | |
| A | | | RELAY, ARMATURE | | | | | | | | | | | | |
| ISSUE | | CHANGED FROM | DATE | CH. NO. | DRAFTS | CHECKER | ENG. APP. | MATERIAL | | J.C. BIELE | | ARB | | | |
| TOLERANCES | | SCALE: S401-59 (33BLAZ9B2) | | TYPE & TEMPER | | HEAT TREAT. SPEC. | | DRAWN | | CHECKED | | FINAL APPROVAL | | | |
| DEC. DIM. ± | | MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES | | FINISH & SPEC. NO. | | ELEC. DES. APP | | MECH. DES. APP | | RL-123 | | | | | |
| FRAC. DIM. ± | | | | | | | | | | | | | | | |
| ANGULAR DIM. ± | | | | | | | | | | | | | | | |