



A ~ 5/32 (.156) DIA. 4 REQ.

REQ. PER. UNIT	USED ON			RL-128	C
	MODEL	AS 'Y. NO.	DATE		
1	GPT 10K	T1-106)	4-9-59		

ELECTRICAL SPECIFICATION

COIL ~ LATCH RELAY ~ 1100 Ω ± 10%
 UNLATCH RELAY ~ 1500 Ω ± 10%
 BOTH COILS MOISTURE RESISTANT
 VARNISHED.

PILE-UP ~ 4 FORM C (4 P.D.T.)

CONTACTS ~ CODE 14 1/4" SILVER
 RATED 20 AMPERES 125V AC RESISTIVE

ADJUSTMENT ~ LATCH-OPERATE-190V ± 5% 60 CYCLE AC OR LESS.
 UNLATCH-OPERATE-.025 AMPERES. DC
 NON OPERATE ~ .023 AMPERES.

NO LONGER AVAILABLE
 REPLACE BY RL 20.5

REF ~ PHILIPS CONTROL CORP. ~ PHILTROL-33BLA29B1

REQ.	ITEM	PART NO.	DESCRIPTION	SYMBOL					
C	NOTE ADD.	10-16-85 22110 GDL	THE TECHNICAL MATERIEL CORP. MAMARONECK, NEW YORK	RELAY, ARMATURE					
B	(DC) Added to UNLATCH	11-10-81 21896							
A	1 ADJ. SPECS. WAS 220V	4.15.64 11215							
ISSUE	ITEM	CHANGED FROM	DATE	CH. NO.	DRAFTS	CHECKER	ENG. APP.		
TOLERANCES			SCALE:						
DEC. DIM. ±			MAXIMUM ALLOWABLE TOLERANCES HAVE BEEN DETERMINED AND ANY DEVIATIONS WILL BE CAUSE FOR REJECTION. REMOVE ALL BURRS AND SHARP EDGES						
FRAC. DIM. ±									
ANGULAR DIM. ±									
TYPE & TEMPER		HEATTREAT. SPEC.		DRAWN		CHECKED		FINAL APPROVAL	
FINISH & SPEC. NO.		ELEC. DES. APP		MECH. DES. APP		RL-128 C			